

# MATERIAL SAFETY DATA SHEET



ASIAN PAINTS EXT WALL PUTTY

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### Identification of the substance or mixture

**Product name** : ASIAN PAINTS EXT WALL PUTTY  
**Product code** : BL-00310908  
**Chemical name** : Not available.  
**Synonyms** : Not available.  
**Chemical formula** : Not applicable.  
**CAS number** : Not applicable.

### Company/undertaking identification

**Manufacturer** : ASIAN PAINTS BANGLADESH LTD.  
PLOT NO. 317 & 757,  
BAHADURPUR, GAZIPUR,  
BANGLADESH.  
Tel. : +880-2-9204482 / 83

**Supplier** : ASIAN PAINTS BANGLADESH LTD.  
PLOT NO. 317 & 757,  
BAHADURPUR, GAZIPUR,  
BANGLADESH.  
Tel. : +880-2-9204482 / 83

**e-mail address of person responsible for this SDS** : xxxxx@xxxxxxx.xxx

**Emergency telephone number (with hours of operation)** : Emergency telephone number (with hours of operation)

## 2. HAZARDS IDENTIFICATION

**Classification** : Corrosive

**Risk phrases** : R35- Causes severe burns.  
R43- May cause sensitization by skin contact.

**Human health hazards** : Causes severe burns. May cause sensitization by skin contact.

**Additional hazards** : None known.

See Section 11 for more detailed information on health effects and symptoms.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance/preparation** : Mixture

| Ingredient name  | CAS number     | %       |
|--|----------------|---------|
| Calcium compounds, Portland cement.  | 65997 - 15 - 1 | 15 - 30 |
| calcium carbonate  | 471-34-1       | 15 - 30 |
| Calcium oxide  | 1305-78-8      | 0 - 1   |
| reaction mass of:<br>5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | 55965-84-9     | 0 - 1   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## 4. FIRST AID MEASURES

- Inhalation** : Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

See Section 11 for more detailed information on health effects and symptoms.

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

- Suitable** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : No specific fire or explosion hazard.
- Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

## 6. ACCIDENTAL RELEASE MEASURES

- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

## 7. HANDLING AND STORAGE

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure limit values

| <u>Ingredient name</u> | <u>Occupational exposure limits</u>  |
|------------------------|--|
| Calcium oxide          | <b>ACGIH TLV (United States, 3/2012).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours.   |
| calcium carbonate      | <b>OSHA PEL (United States, 6/2010).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction<br>TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust   |
| Calcium oxide          | <b>ACGIH TLV (United States, 3/2012).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours.<br><b>OSHA PEL 1989 (United States, 3/1989).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br><b>NIOSH REL (United States, 1/2013).</b><br>TWA: 2 mg/m <sup>3</sup> 10 hours.<br><b>OSHA PEL (United States, 6/2010).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. |

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Exposure controls

- Occupational exposure controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Solid.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Boiling point** : Not available.
- Melting point** : Not available.
- Flash point** : Not available.
- Vapor pressure** : Not available.
- Solubility** : Not available.
- Vapor density** : Not available.
- Auto-ignition temperature** : Not available.
- Density** : 1 g/cm<sup>3</sup>
- Flammability** : Not available.

## 10. STABILITY AND REACTIVITY

- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No known incompatibility

## 11. TOXICOLOGICAL INFORMATION

### Potential acute health effects

- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
- Ingestion** : May cause burns to mouth, throat and stomach.
- Skin contact** : Severely corrosive to the skin. Causes severe burns. May cause sensitization by skin contact.
- Eye contact** : Severely corrosive to the eyes. Causes severe burns.

### Potential chronic health effects

#### Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------|---------|-------|----------|-------------|
|-------------------------|--------|---------|-------|----------|-------------|

## 11. TOXICOLOGICAL INFORMATION

|   |                          |        |   |                         |   |
|---|--------------------------|--------|---|-------------------------|---|
| calcium carbonate   | Eyes - Severe irritant   | Rabbit | - | 24 hours 750 Micrograms | - |
|   | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| reaction mass of:<br>5-chloro-2-methyl-4-isothiazolin-3-one<br>[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Skin - Severe irritant   | Human  | - | 0.01 Percent            | - |

**Chronic effects** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Inhalation** : No specific data.

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Skin** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur

**Eyes** : Adverse symptoms may include the following:  
pain  
watering  
redness

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

**Conclusion/Summary** : Not available.

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------|--------------------|------|-----------|
| Calcium oxide           | -                  | 2.34 | low       |

**Other adverse effects** : No known significant effects or critical hazards.

## 13. DISPOSAL CONSIDERATIONS

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. TRANSPORT INFORMATION

### International transport regulations

This preparation is not classified as dangerous according to international transport regulations (ADR/RID, ADNR, IMDG and IATA ). Transport in accordance with ADR/RID, ADNR, IMDG and IATA and national regulation.

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

## 15. REGULATORY INFORMATION

Hazard symbol or symbols :



Corrosive

Risk phrases

: R35- Causes severe burns.  
R43- May cause sensitization by skin contact.

Safety phrases

: S1/2- Keep locked up and out of the reach of children.  
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.  
S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Contains

: Calcium compounds, Portland cement.  
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Product use

: Consumer applications.

## 16. OTHER INFORMATION

National Fire Protection Association (U.S.A.) :



### History

Date of printing : 05-01-2023.  
Date of issue/ Date of revision : 05-01-2023.  
Date of previous issue : No previous validation.  
Version : 2

Indicates information that has changed from previously issued version.

### Disclaimer

Information contained in this material safety data sheet is believed to be reliable and given in good faith, but no representation, guarantee or warranties of any kind are made as to its accuracy, suitability for a particular application or results to be obtained from them.

The user of this material decides what safety measures are necessary to safely use this material, either alone or in combination with other materials.

Asian Paints Limited makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

**ASIAN PAINTS EXT WALL PUTTY**