

Texolite Apcopaste White

DESCRIPTION

TEXOLITE APCOPASTE WHITE is an APEO free ready to use pigment paste based on special styrene acrylic co polymer. Pigment pastes for textiles are concentrated dispersions of solid pigment particles in a liquid carrier, specifically designed for coloring and decorating fabrics. These pigment pastes are commonly used in the textile industry for applications like screen printing, block printing, and direct printing on fabrics. "TEXOLITE APCOPASTE WHITE" offers several advantages, including color consistency and ease of application. Here are some key aspects of pigment pastes for textiles:

KEY FEATURES

- Excellent hiding ability (Pigment shade will not be affected by the color of the base fabrics)
- Excellent application properties.
- Suitably designed for short Printing.
- Excellent rubbing fastness, washing fastness and water resistance.
- Excellent soft to hand touch.
- Excellent brightness and whiteness.
- Suitable for printing on knitted and woven fabrics.

Typical Properties (Physical and Chemical Properties)

Property	Typical Values
Appearance	Bright white paste
pH value	(8.5 – 9.5) at 30°C
Viscosity (cps)	(4,000 to 5,000) at 30°C, SP 02, RPM 562
Solid Content	(65 ± 5) %
Specific Gravity	(1.52 ± 0.05) at 30°C
Stability/Compatibility	Very much compatible with the auxiliaries usually applied in printing process.

APPLICATION USAGE:

- This paste can be applied directly through an auto screen rotary machine or flat-bed printing machine.
- No dilution with water to reduce the viscosity.
- Before use, please stir the product well.
- Rubbing and washing tests should be performed 24 hours after curing.

HANDLING & STORAGE

Conditions for safe storage: Keep from freezing - product stability may be affected. **STIR WELL BEFORE USE.** Containers once opened should be consumed immediately and shut tightly to prevent contamination. Sanitize with sanitization solution after cleaning of used up containers.

Storage stability Storage temperature: 15-30 °C

PRECAUTIONS FOR SAFE HANDLING

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas. Transport & storage should be performed under shade, cleaned & closed area and away from heat sources at all time. Use PPE (Hand gloves, Goggles, cleaned cloth & shoe etc) during filling and transfer to prevent human contact with product. Product's transfer should be performed in clean & properly sanitized transfer lines and pumps.

DISPOSAL

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed of in a safe and legal manner.

STORAGE LIFE

Twelve months (max.) in sealed container, stored away from direct heat & sunlight in well-ventilated area.

PACK SIZE

25 KG and 125 KG plastic container

Ø ZDHC
Zero Discharge of
Hazardous Chemicals





For enquiries, feedback and complaints,
please call toll-free number **09612003355** or write
to us at weassure.apbl@asianpaints.com

Asian Paints Bangladesh Ltd.

Head Office: The Pearl Trade Centre (PTC), Cha-90/3, Progoti Sarani, North Badda, Dhaka - 1212. Phone: 09612003355

Factory & Registered Office: Gazipur Factory: Plot# 317 & 757, Bahadurpur, Gazipur-1703 | Mirsarai Factory: Plot # 36, Zone 6, Mirsarai Economic Zone, Chittagong - 4324