

Breemo Alkyd Topcoat

Alkyd topcoat

DESCRIPTION & USES

- **Breemo Alkyd Topcoat** is a modified alkyd resin-based single component topcoat formulated to apply on steel and wood after suitable priming. Suitable for protection of structural steel in moderate corrosive environments.
- Semigloss finish and reasonably fast drying properties.
- For Exterior and Interior use depending on color.

PROPERTIES

Finish	Smooth/ Semigloss
Color	White and selected RAL colors on request.
% Solid Content by volume	55 ± 3 Varies depending on color
Diluent/Thinner	Breemo thinner ST1
Drying Time at 25°C and relative humidity 50%	• Touch Dry : 2 hour max • Dry to handle : 5 hours max
Recommended DFT	40 - 50 µm (multiple coats may be required)

INSTRUCTIONS FOR USE

- Steel surface must be free from oil, grease, dirt, & other contaminants.
- Remove loose scale & rust by manual wire brush or suitable mechanical cleaning.
- Prime as soon as possible after surface preparation and apply **BREEMO STEEL ZP**
- Apply two coats of Breemo Alkyd topcoat with recoating interval of overnight.
- Use in good ventilated areas and keep away from source of ignition as the product is flammable.

APPLICATION TOOLS

Brush - Roller – Conventional Spray and Airless Spray Gun

THEORETICAL COVERAGE

13.75 m²/L at 40 microns. Practical coverage varies depending on film thickness, surface porosity and losses.

PACKAGING

Available in 20 liters, special packs available on request.

STORAGE & SHELF-LIFE

12 months in original tightly closed packs away from direct sunlight and excessive heat

Refer safety data sheet before using the product.

Contact SCIB representative for further clarifications.