



WATER BASED

asianpaints

No Added Mercury, Arsenic & Chromium

Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

Asian Paints Premium Emulsion provides a rich and smooth finish for interior walls. Its composition imparts excellent durability to the paint film, giving your walls that 'just painted' look year after year.

Asian Paints Premium Emulsion is washable and most stains can be removed easily by sponging with a mild soap solution. The Paint film is also fungus and mildew resistant.


PRODUCT FEATURES

AVAILABLE PACKS



Shelf-life: 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

SHADE RANGE



As per Colourworld Fandek.

COVERAGE

On smooth primer masonry surface by brushing



**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

RECOMMENDED USAGE

Asian Paints Premium Emulsion is an interior wall finish that can be applied on all types of smooth plasters, false ceilings, asbestos sheets, concrete, etc.

RECOMMENDED APPLICATION

Apply 2 coats of Premium Emulsion for repainting and 3 coats for fresh surface painting as given below:

PRODUCT	CODE	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
<ul style="list-style-type: none"> Sand the surface with Emery Paper 180 and wipe clean 					
<ul style="list-style-type: none"> Asian Paints Wall Primer Brush, Spray 	0359	Mineral Turpentine Oil or Water	<ul style="list-style-type: none"> 8-10 15-20 	<ul style="list-style-type: none"> 30-40 20-25 	6-8 hrs
<ul style="list-style-type: none"> Asian Paints Acrylic Wall Putty Putty Knife 	1354	Water	As reqd	N.A.	4-6 hrs
<ul style="list-style-type: none"> Sand with Emery Paper 180 and wipe clean 					
<ul style="list-style-type: none"> Asian Paints Wall Primer Brush, Spray 	0359	Mineral Turpentine Oil or Water	<ul style="list-style-type: none"> 8-10 15-20 	<ul style="list-style-type: none"> 30-40 20-25 	6-8 hrs
<ul style="list-style-type: none"> Sand with Emery Paper 320 and wipe clean 					
<ul style="list-style-type: none"> Asian Paints Premium Emulsion 1st coat Brush, Roller, Spray 	0011	Water	<ul style="list-style-type: none"> 60-70 70-75 	<ul style="list-style-type: none"> 20-30 20-25 	3-4 hrs
<ul style="list-style-type: none"> Asian Paints Premium Emulsion 2nd coat Brush, Roller, Spray 	0011	Water	<ul style="list-style-type: none"> 60-70 70-75 	<ul style="list-style-type: none"> 30-45 22-25 	3-4 hrs

*Recoat period is quoted for 28-30°C and 60-65% Relative Humidity, these may vary under different conditions.

Spraying Air Pressure 2.75 to 3.5 Kgs/sq cm

Spray Brush

ADDITIONAL INFORMATION

POST PAINTING CARE

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.

TECHNICAL DETAILS

- a) Drying Time : Surface Dry time 10 - 15 minutes
- b) Gloss Levels/Sheen Levels : 15-18 on glass plate at 85°
- c) Flash Point (IS 101/1987, Part 1, Sec 6) : Premium Emulsion is a water based paint which is not flammable.
- d) Stability of Thinned Paint : Use within 24 hrs.

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Premium Emulsion which gives detailed information on safety measures while handling the paint.
- > Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- > Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- > Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both the cases.
- > Use protective equipments like rubber/polythene gloves, safety goggles/glasses, face mask while handling the paint-this is required for all paints.
- > In high-humidity areas, use of a bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.
- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Tinted paints need thorough shaking/mixing immediately after tinter addition as well as before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.



For enquiries, feedback and complaints,
please call toll-free number
16600124680/9802033515 or write to us at
weassure@asianpaints.com.np