

PREMIUM GLOSS ENAMEL

ASIAN PAINTS APCOLITE PREMIUM GLOSS ENAMEL IS A SOLVENT BASED FINISH.



WATER BASED

asianpaints

No Added Mercury, Arsenic & Chromium


Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

Asian Paints Apcolite Premium Gloss Enamel imparts a shiny new look to surfaces painted with this finish. It forms a tough film that is extremely resistant to stains and water. It there by serves as a protective armour around the painted surface.


PRODUCT FEATURES

AVAILABLE PACKS



Shelf-life: 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

SHADE RANGE



Currently available in more than 1100 shades as per the Colourworld Fandack.

COVERAGE

On smooth primed mild steel surface by brushing



1 COAT
16 - 22
sq.mtr/ltr



2 COATS
9 - 11
sq.mtr/ltr

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

RECOMMENDED USAGE

Asian paints apcolite premium gloss enamel can be used on interior and exterior surfaces. Specifically, it can be applied on wooden surfaces like doors, windows, cabinets, on metal surfaces like grills, gates and on suitably prepared masonry wall surfaces.

RECOMMENDED APPLICATION

CLEANING : Prepare the surface by sanding with Emery Paper 180. Wipe clean.

Apply topcoats of as follows:

PRODUCT	CODE	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
Sand with Emery Paper 180 and wipe clean					
Asian Paints Wood Primer or Asian Paints Metal Primer or Asian Paints Wall Primer (Select primer depending on surface) Brush, Roller, Spray	0007 or 0005 or 0359	MTO (Mineral Turpentine Oil)	 8-10  12-15	 30-40  20-25	6-8 hrs
Asian Paints Wall Putty for masonry/cement surfaces or Asian Paints Knifing Paste Filler for wood or metal surfaces Knifing with Putty Blade	1354 or 0016	Water or MTO (Mineral Turpentine Oil)	As Req'd.	As Req'd.	Wall Putty: 4-6 hrs Knifing Paste Filler: 6-8 hrs
Sand with Emery Paper 180 and wipe clean					
Asian Paints Wood Primer or Metal Primer or Wall Primer depending on surface Brush, Roller, Spray	0007 or 0005 or 0359	MTO (Mineral Turpentine Oil)	 8-10  12-15	 30-40  20-25	6-8 hrs
Sand with Emery Paper 320 and wipe clean					
Asian Paints Apcolite Premium Gloss Enamel 1st Coat Brush, Roller, Spray	0001 and 0026	-	 8-10  15-20	 55-60  22-25	6-8 hrs
Asian Paints Apcolite Premium Gloss Enamel 2nd Coat Brush, Roller, Spray	0001 and 0026	MTO (Mineral Turpentine Oil)	 8-10  15-20	 55-60  22-25	6-8 hrs

*Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

Spraying Air Pressure 2.75 to 3.5 Kgs/sq cm. Application Viscosity as measured by Ford Cup B4 at 30°C.

 Spray  Brush

ADDITIONAL INFORMATION

POST PAINTING CARE

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.

TECHNICAL DETAILS

- | | |
|---|--------------------------------|
| a) Drying Time | : Surface Dry time ~ 3 hrs. |
| b) Gloss Levels/Sheen Levels | : 75-85 on tin plate at 20°GH. |
| c) Flash Point (IS 101/1987, Part 1, Sec 6) | : 35°C (95°F). |
| d) Stability of Thinned Paint | : Use within 24 hrs. |

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Apcolite Premium Gloss Enamel which gives detailed information on safety measures while handling the paint.
- > Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire.
- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4hrs of application.
- > Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- > Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if the symptoms persist in both the cases.
- > Use protective equipments like rubber/polythene gloves, safety goggles/glasses, facemask while handling the paint.
- > Tinted paints need thorough shaking immediately after tinter addition as well as before use.
- > Stir well and strain before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.

CONTACT US

Asian Paints (Nepal) Pvt. Ltd.
H.I.D - P. O. Box: 37, Hetauda, Nepal
Ph: 01-5203045, 01-5203046
I.R. No: 1644/40

For more information on our products and services,
visit us at www.asianpaintsnepal.com
For feedback/complaints, write to ccm@asianpaints.com.np
Please note that this data sheet supersedes any previous versions.

