

TOUCHWOOD INTERIOR

ASIAN PAINTS TOUCHWOOD INTERIOR IS A SINGLE PACK POLYURETHANE MODIFIED WOOD FINISH.



 WATER BASED

 **asianpaints**

 No Added Mercury, Arsenic & Chromium

Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

Asian Paints Touchwood Interior is a brushable clear wood finish. It enhances the natural look of wood and offers good resistance to normal wear and tear.

PRODUCT FEATURES

AVAILABLE PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

On smooth sanded wooden surface by brushing



**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

RECOMMENDED USAGE

Asian Paints Touchwood Interior can be used for interior finishing of natural wood and wood veneers.

RECOMMENDED APPLICATION

Select seasoned wood for coating. Sand the wooden surface along the grains using Emery Paper 180. This should be followed by smooth sanding with Emery Paper 320 or 400. Wipe the surface to clean off loose dust particles.

Apply top-coats as follows:

PRODUCT	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
- Asian Paints Touchwood Interior Glossy 1st Coat - Brushing, Spraying	Mineral Turpentine Oil	 0-5  20-25	 30-50  20-25	24 hrs
Sand with Emery Paper 320 or 400 and wipe clean	-	-	-	-
- Asian Paints Touchwood Interior Glossy 2nd Coat - Brushing, Spraying (Apply 3rd Coat if required)	Mineral Turpentine Oil	 0-5  20-25	 30-50  20-25	24 hrs

• If staining is required apply Asian Pints Wood Stain by ragging on sanded wooden surface and allow it to dry for 30 minutes.

NOTE

- Do not store Asian Paints Touchwood Interiors in a half filled container to avoid skin formation. Transfer contents to a smaller container so as to leave no air gap.
- Take care to cap the container tightly after use.
- Asian Paints Wood Stains should not be mixed with Asian Paints Touchwood Interior.
- Asian Paints Touchwood Interior must not be polluted with oil, varnish or the like and must not be sanded with steel wool between coats.

*Recoat time is quoted for 30°C and 75% Relative Humidity, these may vary under different conditions.

Spraying Air Pressure 2.2 to 2.8 Kg/sq cm.

Application Viscosity as measured by Ford Cup B4 at 30°C.

 Spray  Brush

ADDITIONAL INFORMATION

POST PAINTING CARE

For removing stains on tiles and metal surfaces, apply NC thinner on the surface and wipe clean. If stains are difficult to remove, scraping can be done after applying NC Thinner on the stained area. Precautions need to be taken while brushing / spraying like masking of adjoining areas with suitable material, as the stains may be difficult to remove if presents on wood or coated wooden and wall surfaces.

TECHNICAL DETAILS

- | | |
|---|---|
| a. Drying time | : Surface dry time- 1 hour, Tack free time- 4 hours |
| b. Gloss levels/Sheen levels | : 80% minimum (Glossy) and 15-25% (Matt) on coated wooden panel at 60° Gloss Head |
| c. Flash point IS101/1987 Part 1, Sec 6 | : Above 30°C (86°F) |
| d. Stability of thinned paint | : Use within 24 hrs. |

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Touchwood Interior Glossy which gives detailed information on safety measures while handling the paint.
- > Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- > For optimum performance Asian Paints Touchwood Interior must be applied at a temperature between 20° and 40°C and humidity not above 75%.
- > Avoid eye and skin contact. In case of eye and skin contact wash with plenty of clean water.
- > Do not inhale or ingest. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- > Work in well- ventilated area.
- > Use protective equipments like rubber/ polythene gloves, safety goggles / glasses, face mask while handling the paint.
- > Dispose in land filing. Do not dispose in any drain or water- channel.
- > Stir well and strain before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.

CONTACT US

Asian Paints (Nepal) Pvt. Ltd.
H.I.D - P. O. Box: 37, Hetauda, Nepal
Ph: 01-5203045, 01-5203046
I.R. No: 1644/40

For more information on our products and services,
visit us at www.asianpaintsnepal.com
For feedback/complains, write to ccm@asianpaints.com.np
Please note that this data sheet supersedes any previous versions.

