

Royale Luxury Emulsion

Royale Luxury Emulsion is an exquisite interior emulsion paint that delivers luxurious smoothness and a rich high-sheen elegance to your walls. Powered by Advanced Hybrid Polymer Technology, it offers superior stain and scuff resistance, helping walls retain their pristine beauty for years to come.

DESCRIPTION

Anti Scuff Technology

Designed to keep your walls looking as good as new, this feature offers exceptional resistance against everyday marks and abrasions. Whether it's furniture brushing against the surface, or any wooden, plastic or rubber material rubbed over the surface, the coating acts as a protective shield that prevents visible damage.

Unmatched Stain Resistance

It ensures your walls stay pristine and protected against life's everyday spills and mishaps. The advanced formulation creates a strong barrier that prevents stains from settling into the surface from daily household activities. This makes cleaning effortless-most stains can be wiped away with ease, without affecting the paint's finish.

Anti-Fungal Properties

Anti-fungal properties protects the painted surface from fungal growth, preserving the beauty of your walls while contributing to a healthier indoor environment.

Pearl Rich Smoothness

Pearl Rich Smoothness elevates your interiors with a luxurious, smooth finish that mirrors the gentleness of natural pearls. The paint glides effortlessly onto the surface, creating an even, ultra-smooth texture that feels refined to the touch and looks visually stunning.

Green Assure

Green Assure is our promise that the product conforms with international environmental and safety standards. It is low VOC and does not contain hazardous raw material.

Excellent flow

Excellent flow and leveling properties allow smooth, even application delivering a uniform, near brush mark-free finish.

Ultra Rich Experience

More than just aesthetics, it offers a complete sensory experience-where style, comfort, and durability come together.



WATER BASED
asianpaints

No Added Lead, Mercury, Arsenic & Chromium

Lead contents does not exceed 90 parts per million.

PRODUCT FEATURES

AVAILABLE PACKS



Shelf-life: 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

COVERAGE

On smooth primer masonry surface by roller.




2 COATS
100-120sqft/ltr**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

COLOURS AVAILABLE

1578 SHADES*



*Currently available in more than 1578 shades as per the Asian Paints Colour Spectra.

FINISH


MATT RICH MATT SOFT SHEEN **HIGH SHEEN** ULTRA SHEEN

✓ **SMOOTH**

Refer to gloss levels in technical details

HOW TO APPLY

PRE PAINTING STEPS



PLASTER New masonry surfaces must be allowed to cure completely. It is recommended to allow 3 months as the curing time for new masonry surfaces.



PLASTER For filling cracks upto 5mm use Asian Paints Crack Seal.



CLEANING Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness, correct it to limit further dampness. Bio block can be used for removing fungus, algae or moss. 2 coats of Smart Care Salt Clean can be used to remove efflorescence, followed by wet sponge mopping.



FILLING FOR HOLES & DENTS For larger dents/holes it is recommended to use cement and fine sand in the ratio 1:3 mixed with latex xtreme+, 7% by weight of cement.

RECOMMENDED APPLICATION

Apply 2 coats for light shades and 3 coats for dark shades.

APPLICATION	CODE	THINNER	DILUTION	RECOATING PERIOD
SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN				
USE DECOPRIME CEMENT PRIMER WHITE - WT	8360	 WATER	50%-60%	4-6 HRS
OR				
ASIAN PAINTS ROYALE BASE COAT	8033	 WATER	10%	4-6 HRS
ASIAN PAINTS ACRYLIC WALL PUTTY/ASIAN WALL PUTTY/SMARTCARE WATERPROOF WALL PUTTY	8753/8079/8077	 WATER	AS REQD	6-8 HRS
SAND WITH EMERY PAPER 180 AND WIPE CLEAN				
ASIAN PAINTS ACRYLIC WALL PUTTY/ASIAN WALL PUTTY/SMARTCARE WATERPROOF WALL PUTTY	8753/8079/8077	 WATER	AS REQD	6-8 HRS
SAND WITH EMERY PAPER 320 AND WIPE CLEAN				
USE DECOPRIME CEMENT PRIMER WHITE - WT	8360	 WATER	50%-60%	4-6 HRS
OR				
ASIAN PAINTS ROYALE BASE COAT	8033	 WATER	10%	4-6 HRS
SAND WITH EMERY PAPER 320 AND WIPE CLEAN				
APPLY 1 st COAT OF ROYALE LUXURY EMULSION	8030	 WATER	25%-35%	4-6 HRS
SAND WITH EMERY PAPER 400 AND WIPE CLEAN				
APPLY 2 nd COAT OF ROYALE LUXURY EMULSION	8030	 WATER	25%-35%	4-6 HRS

In case of surfaces which have dampness issues or chances of moisture ingress in future, it is highly recommended to use Smart Care Damp Block 2K (2-3 coats) before starting normal paint application.

*Dilution measured on volume basis. Recoat period is quoted for 25°C. And 50% relative humidity.

ADDITIONAL INFORMATION

POST PAINTING CARE

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.

TECHNICAL DETAILS

- Drying Time:**
Surface dry (touch dry) - 30 to 45 minutes.
- Gloss Levels/Sheen Levels:**
33-38 on glass plate at 85° angle (Sliky smooth with sheen)
- Flash Point (IS 101/1987, Part 1, Sec 6):**
Royale is a water based paint which is not flammable
- Stability of Thinned Paint:**
Use within 24 hrs.

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Royale Luxury Sheen Emulsion which gives detailed information on safety measures while handling the paint.
- > Store the product at ambient conditions in well ventilated location and away from source of ignition and fire.
- > Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- > Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both the cases.
- > Use protective equipments like rubber/polythene gloves, safety goggles/glasses, face mask while handling the paint-this is required for all paints.
- > In high-humidity areas, use of a bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.
- > Do not apply when ambient temperature is less than 10 C or if the temperature might drop to this level within 4 hrs of application.
- > Tinted paints need thorough shaking/mixing immediately after tinter addition as well as before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Lead, Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.



For enquiries, feedback and complaints, please call toll-free number 16600124680/9802033515 or write us at weassure@asianpaints.com.np