

royale PLAY

SPECIAL EFFECTS PAINT

ASIAN PAINTS ROYALE PLAY IS A WATER-BASED SPECIAL EFFECTS PAINT THAT CREATES A VARIETY OF SPECIAL EFFECTS ON THE INTERIOR WALLS.



WATER BASED

asianpaints

No Added Mercury, Arsenic & Chromium

Lead contents does not exceed 90 parts per million.

PRODUCT BENEFITS

SPECIAL EFFECTS

Different types of Special effects such as Crinkle, Dapple, Weaving, Canvas, Spatula, Colourwash, Ragging, Sponging, Combing, Brushing can be created using a variety of tools on Asian Paints Royale Play Special Effects Paint.

EASY APPLICATION

This product has been specifically formulated such that it is easy to apply, allows the tools to move smoothly without much effort, retaining the pattern left by the tool that created it. It provides greater open time to allow the creation of the effect.

SHEEN

It has a soft sheen that lends elegance and style to a surface.

CO-POLYMER, EMULSION BASED, ENVIRONMENT FRIENDLY

Asian Paints Royale Play is a co-polymer emulsion based paint for interior application. It will not run or sag on vertical surfaces. It is abrasion resistant, translucent, odourless, non-toxic, non-flammable and completely health and environment friendly.

PRODUCT FEATURES

FINISH




Tough Texture: Lasts long and ensures low maintenance

AVAILABLE PACKS



Shelf life: 2 years from date of manufacture in original tightly closed containers kept away from direct sunlight and excessive heat.

SHADE RANGE



As per Royale Play Decor Book.

COVERAGE

On smooth well-prepared surface followed by application of Asian Paints Royale Play as recommended in

1 COAT
9.3 - 16.3
sq.m./ltr**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application, special effect created, skill of the applicator and environmental conditions of temperature and relative humidity respectively.

RECOMMENDED USAGE

Asian Paints Royale Play Special Effects Paint is an interior emulsion that can be applied on smooth plasters, asbestos sheets, concrete and on prepared wood etc.

RECOMMENDED APPLICATION

Basecoat -Apply 2 coats of Royale Luxury Emulsion for repainting & 3 coats for fresh surface painting.

Apply 1 coat of Royale Play Special Effects Paint as Topcoat on a well-prepared surface as given below:

PRODUCT	CODE	THINNER	DILUTION% (BY VOL)	APPLICATION VISCOSITY (SEC)	RECOATING* PERIOD (HRS)
• Sand the surface with Emery Paper 180 and wipe clean					
• Asian Paints Wall Primer Brush, Spray	0359	Mineral Turpentine Oil or Water	8-10 15-20	30-40 20-25	6-8 hrs
• Asian Paints Acrylic Wall Putty	1354	Water	As reqd	N.A.	4-6 hrs
• Sand the surface with Emery Paper 180 and wipe clean					
• Asian Paints Wall Primer	0359	Mineral Turpentine Oil or Water	8-10 15-20	30-40 20-25	6-8 hrs
• Sand with Emery Paper 320 and wipe clean					
• Basecoat - Asian Paints Royale Luxury Emulsion 1st coat (Brush, Roller)	030	Water	40-45 65-70	30-45 22-25	3-4 hrs
• Basecoat - Asian Paints Royale Luxury Emulsion 2nd coat(Brush, Roller)***	030	Water	40-45 65-70	30-45 22-25	3-4 hrs
• Topcoat - Asian Paints Royale Play Special Effects Paints. Create the desired effect using appropriate Asian Paints Special Effects Tool.	0069	As such or water	5% water v/v only if required	300-500 gms for roller & brush followed by tools.	N.A.

* All Asian Paints decorative products do not contain any added Mercury, Arsenic and Chromium from April 2008.

** Recoat period have been quoted for 28-30°C and 60-65% Relative Humidity, these may vary under different conditions.

*** Apply a 3rd coat of Royale Luxury Emulsion as Basecoat if required.

Spray Brush

ADDITIONAL INFORMATION

POST PAINTING CARE

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 2 weeks before cleaning.

TECHNICAL DETAILS

- | | |
|-------------------------------|--|
| a) Drying Time | : Surface Dry time - 45-90 minutes at 30±1°C at 60-80 RH |
| b) Gloss Levels/Sheen Levels | : 17-27 on glass plate at 60° |
| c) Flash Point | : It is a water-based paint which is not flammable. (IS 101/1987, Part 1, Sec 6) |
| d) Stability of Thinned Paint | : Use within 24 hrs. |

PRECAUTIONS

- > Kindly refer to the MSDS for Asian Paints Royale Play Special Effects Paint which gives detailed information on safety measures while handling the paint.
- > Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- > Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water.
- > Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both the cases.
- > Use protective equipments like rubber/polythene gloves, safety goggles/glasses, face mask while handling the paint-this is required for all paints.
- > In high-humidity areas, use of a bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.
- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Tinted paints need thorough shaking/mixing immediately after tinter addition as well as before use.

SAFETY AND ENVIRONMENT FEATURES

- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- > In case of skin contact, immediately wash skin with soap and plenty of clean water. Get medical attention, if irritation develops or persists.
- > Do not breathe vapor or spray. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth and dispose through authorized agency for waste management.
- > No added Mercury, Arsenic, Chromium & Ammonia compounds.
- > Left-Over paint disposal:
 - Left-over paint/drums should not be disposed in soil/drains. Consumer should consult a local recycling agency for disposal of paint/drums.
 - The pails/drums should not be used for storing food items.

CONTACT US

Asian Paints (Nepal) Pvt. Ltd.
H.I.D - P. O. Box: 37, Hetauda, Nepal
Ph: 01-5203045, 01-5203046
I.R. No: 1644/40

For more information on our products and services,
visit us at www.asianpaintsnepal.com
For feedback/complaints, write to ccm@asianpaints.com.np
Please note that this data sheet supersedes any previous versions.

