

PRODUCT CODE 8493

Ultima Essence

Asian Paints Ultima Essence is a water thinnable, high quality exterior textured coating with acrylic coating containing high quality aggregates. With its unique engraved finish, it offers a wide range of patterns that combines decoration and protection.

PRODUCT BENEFITS

For exterior surfaces, ensure system application of Ultima Essence followed by Ultima Clear to achieve optimal anti-algal protection. Warranty of 7 years is applicable only when both products are used together as a system.

Dirt Repellent

Ultima Essence's advanced dirt repellent properties ensure the walls prevent dirt, thus keeping them pristine and clean for longer.

Flexible

It offers a flexible coating with crack bridging properties, flexing with extremes in temperature, thereby keeping walls crack free.

Anti-Carbonation

It offers anti-carbonation protection, a non-porous film which prevents carbon dioxide from entering the walls and causing corrosion.




asianpaints




Lead contents does not exceed 90 parts per million.

PRODUCT FEATURES

FINISH



Single Tone Finish




Double Tone Finish



Triple Tone Finish

Tough Texture: Lasts long and ensures low maintenance

COLOURS AVAILABLE



As per Ultima Essence shade card

AVAILABLE PACKS



Shelf life: 2 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

System 1: Single Tone Finish

Basecoat: Ultima Essence shade 1- 1 Coat applied by roller

110 sq ft/ltr**

Spray coat: Ultima Essence shade 1- 1 Coat applied by spray gun

60 sq ft/ltr**

System 2: Double Tone Finish

Basecoat: Ultima Essence shade 1- 1 Coat applied by roller

110 sq ft/ltr**

Spray coat: Ultima Essence shade 1- 1 Coat applied by spray gun

60 sq ft/ltr**

Spray coat: Ultima Essence shade 2 - 1 Coat applied by spray gun

90 sq ft/ltr**

System 3: Triple Tone Finish

Basecoat: Ultima Essence shade 1- 1 Coat applied by roller

110 sq ft/ltr**

Spray coat: Ultima Essence shade 1- 1 Coat applied by spray gun

60 sq ft/ltr**

Spray coat: Ultima Essence shade 2 - 1 Coat applied by spray gun

90 sq ft/ltr**


Spray coat: Ultima Essence shade 3 - 1 Coat applied by spray gun

80 sq ft/ltr**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

HOW TO APPLY

PRE PAINTING STEPS



PLASTER New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



CLEANING Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Asian Paints SmartCare DampBlock to limit further dampness.



FILLING FOR CRACKS For filling cracks upto 3mm use Asian Paints SmartCare Crack Seal.



FILLING FOR HOLES & DENTS In case of dents and holes use Asian Paints Wall Putty or white cement and fine sand in the ratio 1:3

Ultima Essence should not be applied on surfaces / substrates that are subjected to continuous seepage or dampness.

PAINT APPLICATION PROCESS

Step 1:

Primer: Post pre painting steps implemented. Apply 1 coat of Asian Paints Exterior Primer and let dry for 4- 6 hours depending upon the requirement based on temperature.

Step 2:

System 1: Single Tone finish

Basecoat (Priming Coat):

Ultima Essence shade 1 : One Coat applied by roller

Spray coat: Ultima Essence Shade 1 : One coat applied by spray gun at high pressure

System 2: Double Tone finish

Basecoat (Priming Coat):

Ultima Essence shade 1 : One Coat applied by roller

Spray coat:

Ultima Essence Shade 1 : One coat applied by spray gun at high pressure

Ultima Essence Shade 2 : One coat applied by spray gun at normal pressure

System 3: Triple Tone finish

Basecoat (Priming Coat):

Ultima Essence shade 1 : One Coat applied by roller

Spray coat:

Ultima Essence Shade 1 : One coat applied by spray gun at high pressure

Ultima Essence Shade 2 : One coat applied by spray gun at normal pressure

Ultima Essence Shade 3 : One coat applied by spray gun at normal pressure

HOW TO CHOOSE COLOURS

Refer to Ultima Essence Shade book for shade availability. The listed shades can be found in Spectra fandeck as well for exact shade match.



ADDITIONAL INFORMATION

PRECAUTIONS

- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Use of Universal Stainers or colourants is not recommended.
- > Do not keep material open for a long time.
- > Product cannot be applied on surfaces/substrates that are subjected to continuous seepage or dampness.
- > Stir well before use.

POST PAINTING CARE

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

TECHNICAL DETAILS

- a. Drying time:** Surface dry time 30 - 60 min
- b. Flash point IS101/1987 Part 1, Sec 6:** NA

SAFETY FEATURES

- > Kindly refer to the MSDS for Ultima Essence which gives detailed information on safety measures while handling the paint, which is available on request.
- > Store the container with the lid tightly closed in an upright position, in a cool, dry place
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- > Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth.
- > No added Lead, Mercury or Chromium compounds.



For enquiries, feedback and complaints, please call toll-free number 16600124680/9802033515 or write us at weassure@asianpaints.com.np