

Technical Data Primers and Ancillaries

Value Stucco

Product Description

An acrylic co-polymer based filler containing alkali resisting pigments, for the filling of surface irregularities and indentations, hairline surface cracks etc. It helps to produce a smooth and level surface prior to painting.

Recommended Areas of Application

Area of Use	: Interior
Substrate	: Concrete, Plaster, Masonry, Gypsum, may also be used on Timber.

Technical Data

Sheen Variants	: Smooth
Colours	: White
Volume Solids	: 52% ± 2%
Theoretical Covering Capacity	: Solely dependent on the surface profile and the extent of filling required. However, as a guidance only 2-3 m ² /Kg may be considered for a reasonably smooth plastered surface.
Practical Covering Capacity	: For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

	Substrate Temperature	Touch Dry	Overcoating Interval	
			Minimum	Maximum
Drying time	25°C	1 hour	4 hours	Indefinite
	35°C	1 hour	4 hours	Indefinite
	45°C	1 hour	4 hours	Indefinite

Application Data

Method of application	: Trowel, spatula or putty knife
Thinner	: Not required
Thinning ratio (by vol.)	: N.A.

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution. After drying, one coat of Plastaseal Penetrating Sealer can be applied if required.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

TYPICAL PAINT SYSTEM

1 coat x Alkali Resistant Primer/As recommended by the Company

2 coats x Value Stucco Extra Mix

2 coats x Emulsion as required

For alternate system suggestion please contact Sales Representative

Storage, Safety Information And Precautions

Storage and Handling:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 month is from the date of manufacture.

First-Aid

- Eyes : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin : Wash skin thoroughly with soap and water. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion : Do not induce vomiting. Obtain immediate medical attention.
- Shelf life up to 24 months.
- Dispose in landfill only.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect