

DESCRIPTION

Causeway Kenlux Eggshell Paint is a oil-based paint suitable for use on interior wood and metal. It is easy to apply, washable and resistant to condensation which provides tough, even, soft eggshell finish.

- Midsheen
- Tough
- Durable

TYPICAL USES

- Decorative paints with a wide colour range for coatings on wood, walls and steel gates.
- Also suitable for coatings on steelworks, pipelines and concrete.

APPLICATION

- Apply over primed surfaces
- Method of application
 - Conventional Spray
 - Brush

SURFACE PREPARATION

Recommended Primer

- **Metal:** Anti-Corrosive Primer/ Zinc Phosphate Primer
- **Galvanized Steel & Aluminium:** Etch Primer
- **Masonry/Asbestos:** Alkaline resisting wall primer

APPLICATION INSTRUCTIONS

- Ensure that the correctly primed substrate is free of any dust, oil, and other contaminants before applying the paint.
- Apply a layer of recommended primer and leave overnight before applying the topcoat.
- Dilute the paint to the required viscosity, depending on the method of application.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Lead & other heavy metals.



TECHNICAL DATA SHEET KENLUX EGGSHELL FINISH (WHITE / BLACK)

TECHNICAL DATA

- COLOR : White/Black
- COMPONENTS : Single
- FINISH : Eggshell
- CURING MECHANISM : Oxidation process
- VISCOSITY : 165 - 170 sec Ford cup 4
- SPECIFIC GRAVITY : ~ 1.30+/-0.1
- VOLUME OF SOLIDS : Approximately 55%
- THINNER : Causeway Thinner
- MIXING RATIO : 25% (Brush) / 35% (Spray)
- SPRAY VISCOSITY : 18 sec (Ford 4)
- RECOMMENDED THICKNESS PER COAT : 25-30µm
- THEORETICAL COVERAGE : ~ 13m²/L (Based on 25µm DFT)
- DRYING TIME : 30 minutes (Touch dry)
16 hours (Hard dry)
- RE-COATING INTERVAL : 16 hours
- POT LIFE : N/A
- SHELF LIFE : Best before 24 months

PACKING

- 500 ml
- 1 Litre
- 4 Litres



Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

