

DESCRIPTION

Causeway Kenlux Floor Paint is a one component quick drying floor paint designed for household use. Ideal for use on concrete, stone, brick and wood.

- Good Abrasion & Scrub Resistance.
- Quick Drying.
- Excellent Washability.
- High opacity.

TYPICAL USES

- On properly prepared horizontal masonry, wood & metal surfaces.

APPLICATION

- Apply over primed surfaces
- Method of application
 - Roller
 - Brush

APPLICATION INSTRUCTIONS

- Ensure that the substrate is dry and free of any dust, oil, grease and other contaminants before applying the paint.
- Dilute the paint to the required viscosity, depending on the type of application method employed.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Lead & other heavy metals.

NOTE

Make sure that the newly build cement and concrete floors are dried for at least 3 weeks before apply floor paints.



TECHNICAL DATA SHEET KENLUX FLOOR PAINT

TECHNICAL DATA

○ COLOR	: Green, Black, Red, Brown & grey
○ COMPONENTS	: Single
○ FINISH	: Semi-gloss/Gloss
○ CURING MECHANISM	: Air dry
○ VISCOSITY	: 75 sec (Ford 4)
○ SPECIFIC GRAVITY	: ~ 1.350
○ VOLUME OF SOLIDS	: Approx 52%
○ THINNER	: Causeway Thinner
○ MIXING RATIO	: 15% max
○ SPRAY VISCOSITY	: N/A
○ RECOMMENDED THICKNESS PER COAT	: 40µm
○ THEORETICAL COVERAGE	: ~ 10m ² /L (Based on 40µm DFT)
○ DRYING TIME	: ~ 2 hours (Touch dry) 16 hours (Hard dry)
○ RE-COATING INTERVAL	: 16 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

200 ml ○ 500 ml ○ 1 Litre ○ 4 Litres



Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura,
Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com