

## PRODUCT DESCRIPTION

The Finest enduring rich Matt Finish for the Interiors. Classique RICH MATT emulsion has got the brightest White and HD colours. With an excellent coverage and hiding this product offers a 05 years' performance warranty. Also the low VOC and free from Formaldehyde is safer for the family and perfect choice for your beautiful home



## PRODUCT FEATURES & BENEFITS

### SURFACE



### INTERIOR

### AVAILABLE PACKS



Shelf life: 3 Years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

### COLOURS AVAILABLE

1750+\*



Currently available in Brilliant White and more than 1750 shades as per the Asian Paints Causeway Colour Palette & other colour cards.

### FINISH



SMOOTH

Refer to sheen levels in technical details

### COVERAGE

On normal masonry surface by brushing



\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

## HOW TO APPLY

- **Cleaning**-Make surface free from dirt and all other imperfections.
- **Filling and Levelling**-Apply one coat of Asian Paints Causeway Filler and 2 coats of Asian Paints Causeway Putty.
- **Sanding and Priming**-Sand the surface with 150-180 sand paper and then apply second coat of Asian Paints Causeway Filler. SmartCare Damp Seal is recommended as an undercoat for Classique RICH MATT to provide stronger paint film adhesion and give 30% extra coverage.
- **Painting**-Apply 2 coats of Paint as required by diluting with 35-40% water. Allow 3 - 4 hours drying between coats.

\*Actual Coverage may differ from the quoted coverage due to factors such as method and condition of application and surface roughness & porosity.

## PRE PAINTING STEPS



**PLASTER** New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



**FILLING FOR CRACKS** For filling cracks upto 3mm use Asian Paints Causeway SmartCare Crack Seal.



**CLEANING** Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Asian Paints Causeway SmartCare DampBlock to limit further dampness. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use Asian Paints Causeway SmartCare Exterior Sealer.



**FILLING FOR HOLES & DENTS** In case of dents and holes use Asian Paints Causeway Wall Putty or white cement and fine sand in the ratio 1:3

For exterior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use Asian Paints Causeway SmartCare DampProof Silicon Ceramic, before the top coat application.

## PAINT APPLICATION PROCESS

Product	Thinner	Dilution % (by vol)	Re coating* Period (hrs)
Sand the Surface with Emery paper 180 and wipe clean Asian Paints Causeway Acrylic wall filler Brush or Roller	Water	40 - 50	3 - 4 hrs
Asian Paints Causeway Wall Putty by Trowel Sand the surface with Emery Paper 180 and wipe clean	NA	Ready to use	8 - 12 hrs
Asian Paints Causeway Acrylic Wall Filler Brush or Roller	Water	40 - 50	3 - 4 hrs
Sand the surface with Emery paper Paper 320 and wipe clean			
Asian Paints Causeway Classique RICH MATT 1st Coat Brush or Roller	Water	35 - 40	3 - 4 hrs
Asian Paints Causeway Classique RICH MATT 2nd Coat Brush or Roller	Water	35 - 40	3 - 4 hrs
We recommend SmartCare Damp Seal as an undercoat for Classique RICH MATT to provide extra protection and 30% extra coverage.			
Asian Paints Causeway Smartcare Damp Seal Brush or Roller	Water	10	4 - 6hrs

Add 10% water for Dark Bright colours.

If the surface is porous, it is recommended that 2 coats of Asian Paints Causeway SmartCare Damp Seal needs to be used instead of Asian Paints Causeway Interior Wall Filler. For further details read Asian Paints Causeway SmartCare Damp Seal technical data sheet.

## ADDITIONAL INFORMATION

### TECHNICAL DATA

a). Coverage**	:	20-22 sqm/ Per ltr/ Per Coat
b). Drying Time	:	3 – 4 hours
c). Gloss Levels / Sheen	:	2.5 @ 60 deg

### PRECAUTIONS

- Kindly refer to the MSDS for Asian Paints Causeway Classique RICH MATT Interior Emulsion which gives detailed information on safety measures while handling the paint.
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or over-extended the brush.
- Do not use Asian Paints Causeway Universal Stainers or any other colourants after tinting without an approval from the technical division of Asian Paints Causeway.
- Ensure that horizontal surfaces like top of the windows, ledges and other horizontal surfaces etc. are painted with 3 coats for greater protection.
- Stir well and strain before use.
- Tinted paints needs to be thoroughly shaken immediately after tinter addition as well as before use.

### POST APPLICATION INSTRUCTIONS

A freshly prepared surface should be allowed a drying time of minimum 2 weeks for proper film formation. Subsequently to remove stains, use a sponge and clean with mild detergent solution and wipe the surface. Remove stains within 24 hours to ensure best results

### SAFETY FEATURES

- Non-Flammable
- Kindly refer to the MSDS for Asian Paints Causeway Classique RICH MATT Interior Emulsion which gives detailed informationn of safety measures while handling the paint.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breath vapour or spray. It is recommended to war suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.