

DESCRIPTION

Causeway Aqlac Wood Stain is a water base preservative stain suitable for protecting tannin-rich when used outdoors and indoors. Made using transparent iron oxides which provide good light fastness and also absorb UV radiation. It is specially developed to impart uniform colour to the wooden surface, and at the same time provide depth, clarity and tone to emphasize the underlying wood texture.

- UV Resistant (Does not Fade)
- Quick Drying
- Natural Transparent Colour
- VOC Free, Environment Friendly, Water-based & Odourless

TYPICAL USES

- Wood furniture's, doors, cabinets etc.
- Interior & exterior Wooden Surfaces

APPLICATION INSTRUCTIONS

Surface Preparation	Stain Coat	Drying	Sanding	Second Stain Coat	Drying	Sanding
Sand wood up to 180 grit sand paper (80, 120,180)	Stir well and apply one coat of Causeway Aqlac water based wood stain.	1 - 4 hours (Longer the better. Since drying time depend on environmental climate and temperature	Sand very lightly with 320 grit sand paper and clean the surface well.	Stir well and apply 2 nd coat of Causeway Aqlac water based wood stain.	1 - 4 hours (Longer the better. Since drying time dependent environmental climate and temperature).	Sand very lightly with 800 grit sand paper and clean the surface well.

Previously Painted surface: restore the surface to bare wood by completely removing the old coating and follow the above application instructions.

- Apply well sanded, smooth finish bare wood surface
- Method of application
 - Brush
 - Spray

DO NOT SHAKE BEFORE USE AND STIR UNDER SLOW AGITATION.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting.



TECHNICAL DATA SHEET AQLAC WOOD STAIN (WATER BASE)

TECHNICAL DATA

- COLOR : Mahogany, Burma Teak, Walnut, Jack wood, Larch Teak, Red Wood
- COMPONENTS : Single
- FINISH : Matt finish
- CURING MECHNISM : Air-dry
- VISCOSITY : Ready to use
- SPECIFIC GRAVITY : ~1.05
- VOLUME OF SOLIDS : 9 - 11%
- THINNING : Not required
- MIXING RATIO : N/A
- SPRAY VISCOSITY : As it is
- RECOMMENDED THICKNESS PER COAT : 15 - 20µm (DFT)
- THEORETICAL COVERAGE : ~ 7m² / L (Depends on wood substrate)
- DRYING TIME : 01 - 04 hours (Touch)
24 hours (Hard dry)
- RE-COATING INTERVAL : 04 hours
- POT LIFE : N/A
- SHELF LIFE : Best before 24 months

PACKING

- 500 ml
- 1 Litre
- 4 Litres

Issue Date: 24/10/2016

Rev: 01

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.