DEBEER REFINISH 1-951 Silicone Remover

GENERAL INFORMATION

1-951 Silicone Remover Standard Silicon Remover.

MIXING RATIO

-

GUN SET UP

	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

APPLICATION

-

FLASH OFF AND DRY TIMES

AIR DRY 20°C / 68°F		FORCED DRY 60°C / 140°F	
Flash off	-	Flash off	-
Dust free	-	Dust free	-
Dry to handle	-	Dry to handle	-
Dry to tape	-	Dry to tape	-
Dry to sand	-	Dry to sand	-
Dry to polish	-	Dry to polish	-

SUBSTRATES

Bare Steel, old and new paint systems.

POT LIFE AT 20°C / 68°F

-

COMPONENTS

-

ADDITIVES

-

SURFACE PREPARATION

-

NEXT LAYER

-

PHYSICAL DATA

EU REGULATIONS		
VOC Code		2004/42/IIB(a)(850)759
Product sub category (according directive 2004/42/EC) and max VOC content (ISO 11890-1/2) of the ready to use product.		IIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850 g/l. (2007) This product contains a maximum of 759 g/l VOC.
Chemical Base	Mix of organic solvents	
Physical Properties	Viscosity (RTS)	-
	Specific Gravity (kg/l)	0,76
	Flash Point Closed Cup	9°C / 48,2°F
	Volume % Solids	-
	Economy	-
		-
	Gloss	-
	Colour	-

PROTECTION

Use suitable respiratory protection *(fresh air supply respirator is strongly recommended).*

For more detailed information please visit the following link for the Safety Data Sheet:

https://sds.de-beer.com/en/debeer/choose_localization

CLEAN UP

-

STORAGE/SHELF LIFE

Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).

NOTES

-

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. Unless valspar agrees otherwise in writing, valspar makes no warranties, express or implied, and disclaims all implied warranties including warranties of merchantability or fitness for a particular use or freedom from patent infringement. Valspar will not be liable for any special, incidental or consequential damages. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. © 2012 The Valspar Corporation. All rights reserved.

Revision Date: March 2018

valspar AUTOMOTIVE