## DESCRIPTION

Causeway AQLAC 3in1 Top Coat Exterior combines rich wood stain colour and long protection to your wood in one-step conveniently.
Recommended for Exterior Doors & Windows, Exterior Furniture, Wooden Decks & Sunbeds in resorts.

- Economical
- Water Repellent
- UV Resistant

**3 in 1 (Time Saving)**

1. Seal
2. Stain
3. Topcoat

## SURFACE PREPARATION

*For Previously Stained Wood That Is Not Being Stripped*

1. Before starting, surface must be dry, clean and free of dirt, grease and glue.
2. Sand the wood with 180-320 grit Sandpaper to ensure adhesion. Remove all sanding dust.

*For Stripped, Unstained or Raw Wood*

1. Before starting, surface must be dry, clean and free of dirt, grease and glue.
2. Sand the wood in the direction of the grain 180-320 grit sandpaper until smooth. Remove all sanding dust.

- Fill gaps and defects using AQLAC Wood Putty and sand after dry to get uniform finish.

## APPLICATION

| 1st Coat | 2nd Coat | 3rd Coat (if necessary) |
|---|---|---|
| Stir Well (Do not Shake) the Aqlac 3in1 top coat and Apply the first coat with 5% water dilution. Let Dry 4 Hours, Sand with 800 grit Sandpaper | Apply the second coat (do not dilute). Let Dry 4 Hours. | Sand with 800 grit Sandpaper. Apply the third coat (do not dilute). Let Dry 24 hours before handling. (48 hours prior stacking) |

## HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting.

CAUSEWAY PAINTS

## TECHNICAL DATA SHEET

# AQLAC 3 IN 1 TOP COAT

## TECHNICAL DATA

| | |
|---|---|
| ○ COLOR | : Larch Teak, Mahogany, Burma teak |
| ○ COMPONENTS | : Single |
| ○ FINISH | : Semi Gloss |
| ○ CURING MECHNISM | : Air-dry |
| ○ VISCOSITY | : Ready to use |
| ○ SPECIFIC GRAVITY | : 1.032g/m |
| ○ VOLUME OF SOLIDS | : 40% |
| ○ THINNING | : Water |
| ○ MIXING RATIO | : 5% (Max - if required) |
| ○ SPRAY VISCOSITY | : 20 sec |
| ○ RECOMMENDED THICKNESS PER COAT | : 20-25µm (DFT) |
| ○ THEORETICAL COVERAGE | : ~ 19 m²-20m²/l (depends on substrate) |
| ○ DRYING TIME | : 02-04 hours (Touch ) 24 hours (Hard dry) |
| ○ RE-COATING INTERVAL | : 04 hours |
| ○ POT LIFE | : N/A |
| ○ SHELF LIFE | : best before 24 months |

## PACKING

○ 500 ml ○ 1 Litre ○ 4 Litres

**Issue Date: 24/10/2016** **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.