DESCRIPTION

Causeway Aqlac Wood Putty is a water based, environmental friendly product which can be used to fill up defects on the wooden surfaces with excellent adhesion properties.

A water base Acrylic filler for filling and shaping of small dents or smooth out uneven surfaces.

- Easy to Apply
- High Durability
- Interior & Exterior
- Non shrinking
- Fast drying
- Easy sanding
- Excellent applicability

TYPICAL USES

Filling and shaping of dents, uneven surfaces on the wood panel.

For the decoration of interior wall such as shaping or filling up dents, smooth out uneven surfaces.

APPLICATION

- Fill up the defects on the wood using Causeway Aqlac Wood Putty.
- Allow 2-6 hours drying time and sand the excess putty to get an even finish.
- After completely dried up sand the putty with 180 grit sand paper and apply WB wood stain, lacquer as required.
- All the used technical equipment can be easily clean with hot water.

Note : Number of application & drying time depend on depth & dimension of the defects, temperature and humidity in environment. (Best to keep 24 hours)

- Method of Application
  - Scraper
  - Trowel

SURFACE PREPERATION

- Surface must be clear, dry and sound. Joint Tape could be used to reinforce the joint before application.

APPLICATION INSTRUCTIONS

- Product is ready for use.

TECHNICAL DATA SHEET
AQLAC WOOD PUTTY (WATER BASE)

TECHNICAL DATA

○ COLOR	: Burma Teak, Mahogany, Walnut, Jack Wood, Larch Teak, Red Wood
○ COMPONENTS	: Single
○ FINISH	: Matt
○ CURING MECHANISM	: Air dry
○ VISCOSITY	: 470P at 30^0C
○ SPECIFIC GRAVITY	: 1.7g / ml
○ RECOMMENDED THICKNESS PER COAT	: Less than 3 mm
○ THEORETICAL COVERAGE	: 6 m^2 - 8m^2 (Depending on application Thickness and nature of the surface)
○ RE-COATING INTERVAL	: Min 16 hours at 25^0C
○ Dry time	: Surface Dry : 15 minutes Hard Dry : 12 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

○ 250 g ○ 500 g ○ 1 Kg

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.