Product Data Sheet

Asian Paints Polyurethane Varnish

PRODUCT DESCRIPTION

Asian Paints Polyurethane Varnish is based on blend of Urethane Alkyd that has been specially formulated to provide quick drying high gloss finish for interior woodwork. It provides tough and flexible film for maximum durability.
It is ideal for interior wooden surfaces such as furniture, doors, paneling and exterior frame works etc.

AREAS OF APPLICATION

Wooden articles, furniture, doors, and paneling.

PRODUCT INFORMATION

Pack size	200ml,500 ml, 1 litre, and 4 litre
Shade / Colour range	Clear
Finish	Full gloss
Method of Application	By brush or spray

TECHNICAL INFORMATION/ DATA

Thinner	Asian Paints Mineral Turpentine
Thinning ratio (by vol.)	10 – 20% Asian Paints Mineral Turpentine
Drying time at 30^{0}C	
Surface Dry	2 ½ hours maximum
Hard dry	8 hours
Re-coatable interval	10 - 12 hours
Characteristics	Highly flammable

SURFACE PREPARATION

Select seasoned wood for coating. Surface should be sound, dry, clean and free from oil or grease. Previously varnished wood work should be washed with detergent and whilst wet should be rubbed down with abrasive paper, rinsed, cleaned and allowed to dry.

Defective varnish should be removed completely before painting. Surfaces painted with shellac or lacquer should be stripped back to bare wood

APPLICATIONS DETAILS

On bare wood, apply three coats of polyurethane varnish for best results. Previously painted surfaces in good condition may need only one coat. Allow 10 – 12 hours drying between coats and sand paper slightly with No. '0' sand paper between coats. Can be applied by brush or spray. If too thick to apply, thin down by adding 10% Asian Paints Mineral Turpentine.

SAFETY INFORMATION AND PRECAUTIONS

- Avoid open flame, heat and sparks.
- Use only with adequate ventilation.
- Avoid prolonged breathing of vapour or contact with skin.
- Store in a cool dry place.
- Do not dispose in any drain or water channels.
- Dispose in land filling.

CONTACT US

For further information, or if you have any queries about using this product, please contact our office at:

Asian Paints (Lanka) Ltd.
81, Koralawella Road, Moratuwa.

Ph: 011-2658621-4 Fax: 011-2658200	Website: www.asianpaints.com Email id: contact@asianpaints.lk

DISCLAIMER

Although the facts and suggestion in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.