DESCRIPTION

2 pack Epoxy Marine Paint is a high-performance epoxy paint with very good anticorrosive properties and long-lasting durability. It is resistant to most general household chemicals & oils.
Recommended as protective coating for steel, vehicle underbody, household applications, light duty commercial & industrial applications and for metal protection purpose.

- Two Component Epoxy-Polyamide Cured Coating
- High Performance Gloss Coating.
- High Durability

TYPICAL USES

- Steel Structures (buildings/ bridges)
- Petroleum Refineries/ Oil Tanks
- Power Plants/ Marine installations/ Pipelines

APPLICATION

- Direct Application over a prepared metal surface.
- Method of application
  - Conventional Spray
  - Roller
  - Brush

APPLICATION INSTRUCTIONS

- Surface must be free from all dirt, oil, grease, rust or any other foreign material that adversely affects its adhesion properties.

- Mix the Base and Hardener together thoroughly for few minutes before application. Adjust the viscosity of the paint with epoxy thinner if required before application.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

TECHNICAL DATA SHEET

Epoxy Marine Paint

TECHNICAL DATA

- COLORS : Blue, Red, Green, Beige, White, Black, yellow, Grey
- COMPONENTS : Two
- FINISH : Gloss
- CURING MECHANISM : Chemical reaction Between 2 components
- SPECIFIC GRAVITY (kg/L) : ~ 1.45 base
- THINNER : Causeway Epoxy Thinner (5-10% if required)
- MIXING RATIO (VOLUME) : Base: Hardener = 1:1
- SPRAY VISCOSITY : 15-20 sec (Ford 4)
- RECOMMENDED (DFT) : 50-60 µm
- THEORITICAL COVERAGE : 8-10m²/L (Actual may differ depending on the application and wastage)
- DRYING TIME : 3 hours (Touch dry) 24 hours (Hard dry)
- RE-COATING INTERVAL : 5-6 hours
- POT LIFE : 1-1.5 Hours
- SHELF LIFE : Best before 24 months

PACKING

- 1L (Base: Hardener)

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate,
Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 04/04/2019 **Rev: 01**
The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.