DESCRIPTION

Causeway Epoxy Hardener (1:2) is to curing agent for Causeway Epoxy Primers.

APPLICATION

Used in conjunction with **Causeway Epoxy Primer** on steelworks.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

TECHNICAL DATA SHEET

CAUSEWAY EPOXY PRIMER HARDENER (1:2)

TECHNICAL DATA

- APPEARANCE : Clear liquid
- ODOUR : Mild
- VISCOSITY : ~10 sec Ford cup 4
- SPECIFIC GRAVITY : ~ 1.00+/-0.05
- MIXING RATIO : Epoxy Primer :Hardener=2:1
- SHELF LIFE : Best before 24 months

PACKING

- 2 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.asianpaintscauseway.com

Issue Date: 29/07/2020 **Rev: 02**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.