DESCRIPTION

Causeway Kenlux G.P. Varnish is a general purpose varnish formulated to give tough clear finish, on wood and metal surfaces.

- Good weather Resistance
- Flexible
- Lead safe
- Excellent gloss

TYPICAL USES

Recommended for general household furniture

APPLICATION

- Application method
  - Conventional spray, airless and air assisted spray
  - Brush application also possible

SURFACE PREPARATION

- Ensure surfaces are clean, dry and free from dirt, grease and other contamination.
- On new wood, sand the surface and dust off.
- Old varnished areas should be stripped well back then treated as new wood.

APPLICATION INSTRUCTIONS

- Do not apply in a dusty environment.
- Thin first coat up to 30% by mineral turpentine.
- Apply by brush. Allow to dry for 16 hours.
- Successive coats should be applied as supplied or may be thinned up to 15% with mineral turpentine.
- Apply at least 3 coats of varnish to new wood.
- Sand lightly between coats with 400 grit sandpaper. Dust off.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Led & other heavy metals.

TECHNICAL DATA SHEET

KENLUX GENERAL PURPOSE VARNISH

TECHNICAL DATA

○ COLOR	: Clear
○ COMPONENTS	: Single
○ FINISH	: Gloss
○ CURING MECHANISM	: Oxidative polymerization
○ VISCOSITY	: 120 seconds (Ford 4)
○ SPECIFIC GRAVITY	: ~0.895
○ VOLUME OF SOLIDS	: 40%
○ THINNER	: Causeway Turpentine/ Thinner
○ MIXING RATIO	: 25-30%
○ SPRAY VISCOSITY	: 20 seconds (Ford 4)
○ RECOMMENDED THICKNESS PER COAT	: 25µm (DFT)
○ THEORETICAL COVERAGE	: 14-15m^2/L (25µm DFT)
○ DRYING TIME	: 2 hours (Touch dry) 24 hours (Hard dry)
○ RE-COATING INTERVAL	: 16 hours
○ SHELF LIFE	: Best before 24 months

PACKING

○ 500 ml ○ 1 Litre ○ 4 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 24/10/2016 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.