DESCRIPTION

Causeway Kenlux Aluminium Wood & Metal Primer is specially formulated enamel designed for all interior and exterior wood & metal surfaces as undercoat and protective purposes. (Specially prepared for spraying)

An modified alkyd resin based primer especially for wooden doors & windows.

- Durable Finish
- Seal wooden surfaces

TYPICAL USES

It can also be used as a sealer for aged creosote coated surfaces or as a first coat for Causeway Aluminum paint where two coat aluminum systems is required.

APPLICATION

- Method of application
  - Brush
  - Spray

SURFACE PREPERATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. All surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off.

APPLICATION INSTRUCTIONS

Ready for use. Thinning is not usually necessary. After suitable preparation, the normal recommendation is to apply one or two coats of Causeway Aluminium Wood primer followed by an appropriate Causeway paint system.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Led & other heavy metals.

TECHNICAL DATA SHEET

KENLUX ALUMINUM WOOD & METAL PRIMER

TECHNICAL DATA

○ COLOR	: Aluminium
○ COMPONENTS	: 13% Non-leafing Aluminium pigment/ Alkyd binder
○ FINISH	: Aluminium finish
○ CURING MECHANISM	: Air Drying
○ VISCOSITY	: 60 sec Ford cup 4
○ SPECIFIC GRAVITY	: 0.950+/- 0.020
○ VOLUME OF SOLIDS	: Approximately 50%
○ THINNER	: Not recommended
○ MIXING RATIO	: N/A
○ RECOMMENDED THICKNESS PER COAT	: 35µm (DFT)
○ THEORETICAL COVERAGE	: ~ 14-15m²/L (Based on 35µm DFT)
○ DRYING TIME	: 4 hours (Touch dry) 16 hours (Hard dry)
○ RE-COATING INTERVAL	: 16 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

○ 500 ml ○ 1 Litre ○ 4 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 04/04/2019 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.