DESCRIPTION

Causeway Kenlux Bright Aluminium is specially formulated enamel designed for all interior and exterior wood & metal surfaces for decorative and protective purposes. (Specially prepared for spraying)

An modified alkyd based Bright Aluminum paint with anti-corrosive properties.

- Metallic Finish
- Anti-Corrosive
- Fast Drying

TYPICAL USES

For general use on metal/wood structure, where a durable and lustrous aluminum finish is required. Frequently used in metal fencing & metal grill between roads.

APPLICATION

○ Apply over primed surfaces
○ Method of application

- Conventional Spray
- Roller
- Brush

SURFACE PREPARATION

Recommended Primer

- **Wood**: Aluminium Wood & Metal Primer
- **Metal**: Anti-Corrosive Primer/ Zinc Phosphate Primer
- **Galvanized Steel & Aluminium**: Etch Primer

APPLICATION INSTRUCTIONS

- Apply 1 or 2 coats of Causeway Bright Aluminium paint directly on well prepared surfaces.
- Primer should be applied if necessary.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Led & other heavy metals.

TECHNICAL DATA SHEET
KENLUX BRIGHT ALUMINUM

TECHNICAL DATA

○ COLOR	: Aluminium
○ COMPONENTS	: 13% leafing aluminium Pigment & Alkyd binder
○ FINISH	: Gloss
○ CURING MECHANISM	: Air Dry
○ VISCOSITY	: 20 sec Ford cup 4
○ SPECIFIC GRAVITY	: 0.920+/-0.020
○ VOLUME OF SOLIDS	: Approximately 57%
○ THINNER	: Causeway Turpentine/ Thinner
○ MIXING RATIO	: No thinning - Brush 10% - Spray
○ SPRAY VISCOSITY	: 18 sec (Ford 4)
○ RECOMMENDED THICKNESS PER COAT	: 25µm
○ THEORETICAL COVERAGE	: ~ 16-17m²/L (Based on 25µm DFT)
○ DRYING TIME	: 4 hours (Touch dry) 24 hours (Hard dry)
○ RE-COATING INTERVAL	: 16-24 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

○ 200 ml ○ 500 ml ○ 1 Litre ○ 4 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 04/04/2019 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.