DESCRIPTION

Causeway Kenlux Eggshell Paint is a oil-based paint suitable for use on interior wood and metal. It is easy to apply, washable and resistant to condensation which provides tough, even, soft eggshell finish.

- Midsheen
- Tough
- Durable

TYPICAL USES

- Decorative paints with a wide colour range for coatings on wood, walls and steel gates.
- Also suitable for coatings on steelworks, pipelines and concrete.

APPLICATION

- Apply over primed surfaces
- Method of application
  - Conventional Spray
  - Brush

SURFACE PREPARATION

Recommended Primer

- **Metal**: Anti-Corrosive Primer/ Zinc Phosphate Primer
- **Galvanized Steel & Aluminium**: Etch Primer
- **Masonry/Asbestos**: Alkaline resisting wall primer

APPLICATION INSTRUCTIONS

- Ensure that the correctly primed substrate is free of any dust, oil, and other contaminants before applying the paint.
- Apply a layer of recommended primer and leave overnight before applying the topcoat.
- Dilute the paint to the required viscosity, depending on the method of application.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Led & other heavy metals.

TECHNICAL DATA SHEET
KENLUX EGGSHELL FINISH (WHITE / BLACK)

TECHNICAL DATA

COLOR	: White/Black
COMPONENTS	: Single
FINISH	: Eggshell
CURING MECHANISM	: Oxidation process
VISCOSITY	: 165 - 170 sec Ford cup 4
SPECIFIC GRAVITY	: ~ 1.30+/-0.1
VOLUME OF SOLIDS	: Approximately 55%
THINNER	: Causeway Thinner
MIXING RATIO	: 25% (Brush) / 35% (Spray)
SPRAY VISCOSITY	: 18 sec (Ford 4)
RECOMMENDED THICKNESS PER COAT	: 25-30µm
THEORETICAL COVERAGE	: ~ 13m²/L (Based on 25µm DFT)
DRYING TIME	: 30 minutes (Touch dry) 16 hours (Hard dry)
RE-COATING INTERVAL	: 16 hours
POT LIFE	: N/A
SHELF LIFE	: Best before 24 months

PACKING

○ 500 ml ○ 1 Litre ○ 4 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 04/04/2019 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.