DESCRIPTION

Causeway Kenlux Synthetic Enamel is specially formulated and designed for all interior and exterior wooden and metal surfaces where a gloss finish is desired. Kenlux Synthetic Enamel has high coverage, excellent opacity and it's fast drying.

- Excellent Washability
- Excellent Coverage
- Self-levelling Properties
- High Gloss

TYPICAL USES

- Decorative paints with a wide colour range for coatings on wood, walls and steel gates.
- Also suitable for coatings on steelworks, pipelines and concrete.

APPLICATION

- Apply over primed surfaces
- Method of application
  - Conventional Spray
  - Brush

SURFACE PREPARATION

Recommended Primer

- **Wood:** Aluminium Wood & Metal Primer
- **Metal:** Anti-Corrosive Primer/ Zinc Phosphate Primer
- **Galvanized Steel & Aluminium:** Etch Primer
- **Masonry:** Alkaline resisting wall primer
- **Plastic:** Plastic primer

APPLICATION INSTRUCTIONS

- Ensure that the correctly primed substrate is free of any dust, oil, and other contaminants before applying the paint.
- Apply a layer of recommended primer and leave overnight before applying the topcoat.
- Dilute the paint to the required viscosity, depending on method of application.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. The paint is free of Led & other heavy metals.

TECHNICAL DATA SHEET
KENLUX ENAMEL

SLS 533

TECHNICAL DATA

○ COLOR	: Standard Colours
○ COMPONENTS	: Single
○ FINISH	: High Gloss, Semi-gloss & Matt
○ CURING MECHANISM	: Oxidative polymerization
○ VISCOSITY	: 150 - 160 sec Ford cup 4
○ SPECIFIC GRAVITY	: ~ 1.10
○ VOLUME OF SOLIDS	: Approximately 50%
○ THINNER	: Causeway Turpentine
○ MIXING RATIO	: 25% (Brush) / 40% (Spray)
○ SPRAY VISCOSITY	: 15 sec (Ford 4)
○ RECOMMENDED	: 25µm THICKNESS PER COAT
○ THEORETICAL COVERAGE	: ~ 15-16m²/L (Based on COVERAGE 25µm DFT)
○ DRYING TIME	: 4 hours (Touch dry) 16 hours (Hard dry)
○ RE-COATING INTERVAL	: 16 hours
○ POT LIFE	: N/A
○ SHELF LIFE	: Best before 24 months

PACKING

○ 200 ml ○ 500 ml ○ 1 Litre ○ 4 Litres

Causeway Paints Lanka (Pvt) Ltd.
#15, Noel Mendis Mawatha, Modarawila Industrial Estate, Panadura, Sri Lanka.
M: 038-2240040
W: www.causewaypaints.com

Issue Date: 04/04/2019 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.