## DESCRIPTION

Causeway Hammer Tone Finish is a specialty metallic alkyd coating formulated to give an unique hammer tone effect. It dries quickly and has very good scratch, impact resistance and corrosion resistance.

- Excellent Abrasion Resistance
- Excellent Coverage
- Rapid Air Dry
- Special Hammer Tone Effect

## TYPICAL USES

- Decorative paints with a standard color range to choose from for coatings on steelworks, such as exterior gates, pipelines, furniture & home appliances.

## APPLICATION

- Apply directly or over primed surfaces
- Method of application
  - Conventional Spray
  - Roller Application

## APPLICATION INSTRUCTIONS

- Ensure that the correctly prepared substrate is clear of any dust, oil, and other contaminants before applying the paint.
- Apply a layer of undercoat only if necessary and leave overnight before applying the topcoat.
- Dilute the paint to the required viscosity.
- Standard Colors, not for tinting and mixing.

## HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

CAUSEWAY PAINTS

# TECHNICAL DATA SHEET
# CAUSEWAY HAMMERTONE FINISH

## TECHNICAL DATA

| | |
|---|---|
| ○ COLOR | : Std Hammer tone Colour range |
| ○ COMPONENTS | : Single |
| ○ FINISH | : Hammer tone |
| ○ CURING MECHANISM | : Oxidation process |
| ○ VISCOSITY | : 90 sec Ford cup 4 |
| ○ SPECIFIC GRAVITY | : ~ 1.10 |
| ○ VOLUME OF SOLIDS | : Approximately 50% |
| ○ THINNER | : Causeway Thinner |
| ○ MIXING RATIO | : 10% |
| ○ SPRAY VISCOSITY | : 20 sec (Ford 4) |
| ○ RECOMMENDED THICKNESS PER COAT | : 25-35µm |
| ○ THEORETICAL COVERAGE | : ~ 10-12$m^2$/L (Based on 25µm DFT) |
| ○ DRYING TIME | : 30 minutes (Touch dry) 16 hours (Hard dry) |
| ○ POT LIFE | : N/A |
| ○ SHELF LIFE | : Best before 24 months |

## PACKING

○ 1 Litre ○ 4 Litres


The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.