SMARTCARE CRACK SEAL

Asian Paints Causeway SmartCare Crack Seal is a ready to use fiber glass reinforced crack filling compound for both interior and exterior surfaces. It ensures unmatched crack bridging ability for plaster cracks of up to 3 mm.



WATER BASED

LEAD FREE*GUARANTEE

PRODUCT BENEFITS

Crack filling ability
Strong filling capacity for cracks of up to 3mm witdth.

Flexibility
High elongation film that accommodates movement.

Mechanical strength
Reinforced with glass fibers for superior mechanical strength.

Waterproofing
Water resistant film stops water ingress through cracks.

Adhesion
Very strong adhesion on all absorbent surfaces like plaster, wood, gypsum, POP, asbestos, etc.

Usage
Single pack ready-to-use and easy-to-apply product.

Over coating
Easily over coated by emulsion paints from Asian Paints Causeway

PRODUCT FEATURES

AVAILABLE PACKS



Shelf life : 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COLOURS AVALIABLE



White*
*Please note : SmartCare Crack Seal is an undercoat.

COVERAGE

For plaster crack of 3mm width 5mm depth recommended system is



2 COATS
75 running ft/kg

DRYING TIME TO TOUCH



4-6 HOURS

RECOMMENDED USAGE



Can be used for cracks on all interior and exterior absorbant surface, cracks and gaps caused by drying and shinkage.

HOW TO APPLY

PRE PAINTING STEPS



CLEANING Open the cracks and widen the cracks to form a "V" shaped groove. This will provide a strong base for adhesion of Crack Seal to the substrate. Clean the area thoroughly to free it from dust and loose particles. It is recommended to use a cutter for opening the cracks.

PRIMING Post cleaning apply Primer in the opened cracks. For interior cracks, use Asian Paints Causeway Interior Filler water based Primer and for exterior cracks, use Asian Paints Causeway Exterior Primer (as per regular) dilution mention in Data Sheet.

APPLICATION PROCESS

APPLICATION	CODE	THINNER	DILUTION %	APPLICATION VISCOSITY	RECOATING PERIOD
STEP 1 - FIRST COAT SMARTCARE CRACK SEAL **PUTTY KNIFE / TROWEL**	AP73	N/A	N/A	N/A	4 - 6 Hour
STEP 2 - SECOND COAT SMARTCARE CRACK SEAL **PUTTY KNIFE / TROWEL**	AP73	N/A	N/A	N/A	4 - 6 Hour
STEP 3 LEVELING	LEVEL THE WALL USING ASIAN PAINTS CAUSEWAY WALL PUTTY / EXTERIOR PUTTY				
STEP 4 PRIMER AND TOP COAT	CONTINUE NORMAL PAINTING USING PRIMER AND TOPCOAT				

1. Apply Crack Seal at least 3 cm on either side of the crack for better adhesion
2. Apply an additional coat of Crack Seal in case of severe dampness.
3. For best results, follow the recommended application procedure.

ADDITIONAL INFORMATION

POST PAINTING CARE

For the best performance of the paints, ensure proper washing and cleaning of all algal and fungal growth, If any, at regular intervals of six months.

PRECAUTIONS

- Do not apply for cracks of more than 3mm width.
- Do not apply on wet surfaces.
- Meant for plaster cracks. Do not apply on structural on joint cracks.

TECHNICAL DETAILS

A. Form : Ready to use paste.
B. Density at 25°C : 1.28
C. Drying Time : Minimum 6 hours depending on temperature and humidity.
D. Flash Point : Crack Seal is a water based which is not flammable.
E. Consumption : 75 - 80 running feet / kg / 2 coats (3mm wide and 5mm deep)

SAFETY FEATURES

- Kindly refer to the MSDS for Asian Pants Causeway SmartCare Crack Seal gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool & dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skiin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

Causeway Paints Lanka (Pvt)Ltd.
15, Noel Mendis Mawatha, Moderawila Ind. Est, Panadura, Sri Lanka.
(94) 038 2240040-5, (94) 038 2240046 (94) 038 2243166-9
info.causewaylanka@causewaypaints.com

WeAssure Helpline 0777-272-272