DESCRIPTION

Sunny NC based putty is a economical filler for smoothing of slight dented surfaces. Suitable for steel surfaces & wooden surfaces.

- Economical Filler
- Quick Dry

TYPICAL USES

Recommended for any mild steel surface, which are slightly dented. Such mild steel sheets are used for making steel sheets which are used for making steel furniture, any cast iron article, which has to be made smooth, and all types of vehicles, which need repainting.

Natural wood or wood substitute like plywood, particle board

APPLICATION

By putty knife, spatula or stopping knife

APPLICATION INSTRUCTIONS

- Remove any dust, oil and other contaminants that may affect its adhesive property.
- Use Grade 400 abrasive paper to sand down the old surface if necessary.
- Ensure that all loose old paint flakes are removed before any application of the putty.
- Perform sanding only after the putty is fully dried.

SPECIAL INSTRUCTIONS

Do not apply heavy thick coat to fill up deep dents as the filled area will shrink. For deep or thick application polyester putty should be used before applying NC putty.

HEALTH & SAFETY:

FLAMMABLE. Keep away from source of ignition. Avoid contact with skin and eyes. Wear suitable protection glass and cloths. Ensure adequate ventilation in the area where the product is being applied.

CAUSEWAY PAINTS

TECHNICAL DATA SHEET
SUNNY NC PUTTY

TECHNICAL DATA

○ COLOR	: Grey / Red
○ COMPONENTS	: Single
○ FINISH	: Smooth grey / red
○ CURING MECHANISM	: Air drying
○ VISCOSITY	: 400p-500p
○ SPECIFIC GRAVITY	: 1.24 +/- 0.02
○ VOLUME OF SOLIDS	: App 70 %
○ THINNER	: Not required
○ RECOMMENDED THICKNESS PER COAT	: about 200µm
○ DRYING TIME	: 15 minutes (Surface dry) 24 Hours (Hard dry)
○ SANDING TIME	: 45 minutes (Dry Sand) 24 Hours (Wet sand)
○ SHELF LIFE	: 1 year (unopened)

PACKING

○ 200 ml ○ 500 ml ○ 1 Litre ○ 4 Litres

Issue Date: 24/10/2016 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.