DESCRIPTION

Causeway Plastic Primer 100 will help the paint to adhere onto the plastic substrate. Apply 1 or 2 coats of Causeway plastic primer 100 (as it is) & wait for about 30 minutes to let it dry. Then apply the paint on the primed surface.

- Fast Drying
- Enhance Durability of top Coat

TYPICAL USES

- As primer on vehicle bumpers and other plastic parts.
- As adhesion promoter to be added to paint (about 3%) to improve adhesion.
- Suitable as a primer for most of the plastic substrates.

APPLICATION

- Apply over prepared surfaces
- Method of application
  - Conventional Spray

APPLICATION INSTRUCTIONS

- Ensure that the correctly prepared substrate is clear of any dust, oil, and other contaminants before applying the paint.
- Product is ready to use. Apply two thin coats of plastic primer and leave for 30 minutes before applying the top coat.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

CAUSEWAY PAINTS

TECHNICAL DATA SHEET

CAUSEWAY PLASTIC PRIMER-100

TECHNICAL DATA

○ COLOR	: Clear
○ ODOUR	: Little or none
○ COMPONENTS	: Single
○ FINISH	: Matt
○ CHLORINE CONTENT	: 0.000125 (By wt. %)
○ VISCOSITY	: 1000 (mPa.s/25°C)
○ SPECIFIC GRAVITY	: ~ 0.900
○ THINNER	: Not required
○ DRYING TIME	: 5 minutes (Touch dry) 30 minutes (Hard dry)
○ POT LIFE	: N/A
○ FLASH POINT	: 25^0C
○ SHELF LIFE	: Best before 24 months

PACKING

○ 250 ml ○ 1 Litre

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.