DESCRIPTION

CAUSEWAY UNDERBODY MATT BLACK is a solvent containing under body coating based on bitumen/rubber, and offers lasting and flexible protection from stone chipping and corrosion. After complete drying, the coating exhibits an abrasion-resistance and is also an excellent vibration control material. Also it does not drip and produces no mist.

- Quick Drying
- High Coverage
- Long Term Protection
- Stone Chip Resistant

TYPICAL USES

CAUSEWAY UNDERBODY MATT BLACK is used as an under body coating on passenger cars for areas which are mechanically heavily used. And it is particularly suitable for motor vehicle bodies, wheel casings, front spoilers, car doors, edges, joints, bonnets, rear ends, deck lids, etc.

APPLICATION

The product is applied by Under-body Spray gun or spatula. Due to its excellent sag resistance, the material can be applied up to a high layer thickness.

SURFACE PREPERATION

Surface to be painted with **CAUSEWAY UNDERBODY MATT BLACK (Premium)** have to be cleaned well and rust must be removed. The area must be dry and free of oil, grease, dirt and to great extent free of dust.

APPLICATION INSTRUCTIONS

- Use outdoors or in a well-ventilated area such as an open garage. Mix the contents thoroughly before use. Do not dilute with thinner, apply as it is.
- **CAUSEWAY UNDERBODY MATT BLACK** can be applied by special underbody spray gun in one step up to 4mm layer thickness. After dying over night the vehicle is ready for use again. For full curing 24-36 hours are necessary.

HEALTH & SAFETY

Always keep paint out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks.

CAUSEWAY Paints

TECHNICAL DATA SHEET

CAUSEWAY UNDERBODY MATT BLACK (PREMIUM)

TECHNICAL DATA

○ COLOR	: Black
○ COMPONENTS	: Single
○ FINISH	: Matt
○ CURING MECHANISM	: Air dry
○ VISCOSITY	: 10 poise
○ SPECIFIC GRAVITY	: 1.294
○ VOLUME OF SOLIDS	: 60%
○ THINNER	: Not required
○ MIXING RATIO	: Not required
○ SPRAY VISCOSITY	: Apply as it is
○ RECOMMENDED THICKNESS PER COAT	: As per the requirement
○ THEORETICAL COVERAGE	: Depends on the DFT
○ DRYING TIME	: Touch dry : 30 minutes Hard Dry : 16 hours
○ RE-COATING INTERVAL	: 4 hours
○ SHELF LIFE	: Best before 24 months

PACKING

○ 1 Litre

Issue Date: 24/10/2016 **Rev: 01**

The Technical Data is provided only as general advice. However, since service and applications conditions are beyond our control, we do not accept liability relating to coverage, performance and injury arising from the use of our products based on these data. The above information may vary from time to time and we reserve the right to modify the data without prior notice.