

PRODUCT CODE 9814

Asian Paints Rust-O-Fix Multi-Use Spray

Asian Paints Rust-O-Fix Multi-Use Spray is designed to assist with general maintenance, helping to loosen rusted or stuck parts and remove unwanted residues. This versatile spray is suitable for various applications in auto care, home improvement, and DIY maintenance projects.


Formulated for use on a range of surfaces, it supports cleaning, descaling, and light protection tasks. The spray can is convenient for quick application, whether working on tools, hardware, or household surfaces.




asianpaints
LEAD FREE GUARANTEE

* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

PRODUCT BENEFITS



Helps loosen rusted nuts, bolts, and mechanical parts



Assists in removing sticky residues and surface grime



Handy spray can for convenient application



Practical for both home and workshop use



Suitable for descaling and light cleaning applications



Can be used on metal, tools, automotive parts, and household items (test on an inconspicuous area first)

PRODUCT FEATURES



Cleans Rust & Stops Squeaking



Removes Moisture & Loosens Rusted Parts



Lubricates Mechanical Components



Removes Grease & Cleans Stains

AVAILABLE PACKS



Shelf Life: 18 months from the date of manufacture in original tightly sealed packs away from direct sunlight and excessive heat

COLOURS AVAILABLE

Transparent



AREAS OF APPLICATION

Before



After



ADDITIONAL INFORMATION


PHYSICAL DETAILS

Sub category	Weight (gms) (Mandatory)	Quantity (Mandatory)	Shelf life <1095 Days (Mandatory) (in days)	Length (cms) (Mandatory)	Breadth (cms) (Mandatory)	Height (cms) (Mandatory)	Pack/bottel (Mandatory)	HSN (8 Digit only) (Mandatory)
Rust-O-Fix	170	1	547	5.2	5.2	14.6	Bottle	34031900
Rust-O-Fix	340	1	547	6.5	6.5	17.5	Bottle	34031900

DIRECTIONS FOR USE



Step 1: Shake the container well before use.



Step 2: Point the nozzle towards the area of use and spray sufficiently. Let it soak for 15-20 min.



Step 3: For best and longer protection, do not wipe off or scrub the area after applying the material.

Contents under pressure

Do not puncture or incinerate. Do not expose to temperatures exceeding 45°C. Store away from sunlight Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Keep away from sources of ignition. No smoking! Build-up of explosive mixtures possible without sufficient ventilation. Keep away from reach of children. Do not inhale vapour or spray mist After use, ensure the container is empty, without any residual gas & dispose the container appropriately.