

PRODUCT CODE 9816

Asian Paints Acrylic Spray Paint

Asian Paints ezyCR8 Apcolite DIY Spray Paint offers a convenient way to refresh and decorate multiple surfaces. Designed for DIY enthusiasts, this acrylic spray paint is suitable for use on metal, wood, and properly prepared wall surfaces, providing a smooth and vibrant finish.

This spray format ensures even coverage and easy application. The 12 different shades adds a lively touch to furniture, decorative items, craft projects, and minor repairs, making it a versatile option for both indoor and outdoor use.



asianpaints
LEAD FREE GUARANTEE

* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

PRODUCT BENEFITS

- Compatible with metal, wood, and wall surfaces (when properly prepared)
- Multi-surface use for DIY, home décor, and small repairs
- Easy-to-use spray nozzle for controlled and even application
- Handy for indoor and outdoor projects

PRODUCT FEATURES



Superior
Hiding



Stain
Guard



100% Acrylic
Formulation

AVAILABLE PACKS




400
ML

Shelf Life: 3 years from date of manufacture in original tightly sealed packs away from direct sunlight and excessive heat

COLOURS AVAILABLE

12



AREAS OF APPLICATION



Furniture &
Railings icons



Tool &
Spare Parts



Cabinets &
Shelves



Motor
Bikes



Household
Appliances

ADDITIONAL INFORMATION

PHYSICAL DETAILS

Sub-category	Weight (gms) (MANDATORY)	Quantity (MANDATORY)	Shelf life <1095 Days (MANDATORY) (in days)	Length (cms) (MANDATORY)
Spray Paint	250	1	547	6.5
Breadth (cms) (MANDATORY)	Height(cms) (MANDATORY)	PACK/BOTTEL (MANDATORY)	HSN (8 Digit only) (MANDATORY)	
6.5	20	Bottle	32089090	

DRYING TIME

Surface Dry

5 min

Tack Free

10 min

Hard Dry

18 hrs

*Drying Time is quoted for 25°C and 50% Relative humidity, these may vary under different conditions.

ADDITIONAL INFORMATION

COLOURS AVAILABLE



DIRECTIONS FOR USE



Surface must be clean, dry and free from grease/oil and rust.



Sand the surface with Asian Paints Trustar Sanding Paper 180 for uniform & smooth finish.



Shake the can vigorously before use to ensure colour uniformity and to avoid clogging.



Press nozzle firmly and spray from a distance of 25-30 cm.



Avoid Spraying at one spot for long.




For best results, apply in a to-and-fro motion.



Apply 2-3 coats of Asian Paints ezyCR8 Apcolite Acrylic Spray Paint Recommended time between coats is 5 minutes.



Allow final coat to dry for 48 hours before using the surface.



Clean the spray button after use by inverting the container and spraying in 2-3 short bursts, if still clogged rinse it with thinner.