PRODUCT CODE 1A58

Royale Play Lithos

Royale Play Lithos gives you textured wall finishes inspired by real stones that can transform a space like never before.

WATER BASED

asianpaints LEAD FREE*GUARANTEE

* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

PRODUCT BENEFITS

Special Effects

Natural Stone effects like Sandstone, Slate, Red Stone, Laterite are created using a variety of tools on Asian Paints Royale Play Lithos.

Easy Application

This product has been specifically formulated for easy application, it allows the tools to move smoothly without much effort, retaining the pattern left by the tool.

Environment friendly

Asian Paints Royale Play Lithos is water based paint for interior application. It is a stiff-paint, non-toxic, non- flammable and fully respects people's health and environment.

PRODUCT FEATURES

FINISH

Plateau Black

Earth red

Ancient Stone

Dune Beige

Terra Brown

Mineral Grey

COLOURS AVAILABLE

6



AVAILABLE PACKS

Shelf life: 2 year from date of manufacturing original tightly closed containers stored away from direct sunlight and excessive heat.

COVERAGE

On smooth well-prepared surface by trowel and scraper followed by use of Special Effect Tools

2 COAT
5 - 6
sq.ft/kg**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

HOW TO APPLY

PRE PAINTING STEPS

PLASTER New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Asian Paints SmartCare Damp Block to limit further dampness. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use Asian Paints SmartCare Exterior Sealer.

FILLING FOR CRACKS For filling cracks up to 3mm use Asian Paints SmartCare Crack Seal.

FILLING FOR HOLES & DENTS In case of dents and holes use Asian Paints Acrylic Wall Putty or white cement and fine sand in the ratio 1:3

Royale Play Lithos should not be applied on surfaces / substrates that are subjected to continuous seepage or dampness.

PAINT APPLICATION PROCESS

APPLICATION	CODE	THINNER	DILUTION %	APPLICATION VISCOSITY[1]	RECOATING PERIOD[2]
STEP 1 SANDING	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN				
STEP 2 DECOPRIME CEMENT PRIMER (WT) BRUSH / ROLLER / SPRAY	0360	WATER	BRUSH / ROLLER SPRAY 80% – 100 %	BRUSH / ROLLER 30 - 40 SPRAY 20 - 25	4 - 6 HRS
STEP 3 ACRYLIC WALL PUTTY PUTTY KNIFE	1354	WATER	BASED ON REQUIREMENT	N/A	4 - 6 HRS
STEP 4 SANDING	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN				
STEP 5 DECOPRIME CEMENT PRIMER (WT) BRUSH / ROLLER / SPRAY	0360	WATER	BRUSH / ROLLER SPRAY 80 – 100	BRUSH / ROLLER 30 - 40 SPRAY 20 - 25	4 - 6 HRS
STEP 6 SANDING	SAND THE SURFACE WITH SAND PAPER 220 AND WIPE CLEAN				
STEP 7 ROYALE PLAY LITHOS 2 COATS TROWEL / SCRAPER	1A58	AS SUCH OR WATER	2% - 5% BY WATER IF REQUIRED	N/A	4 - 6 HRS
STEP 8 SANDING	SAND THE SURFACE WITH SAND PAPER 220 AND WIPE CLEAN				
STEP 9 ROYALE PLAY PROTECTIVE COAT PC1 – 2 COATS SPONGE ROLLER COLOURWASH SPONGE	5449 0030*	WATER	200 % BY WATER FOR PC1 40 % BY WATER FOR 0030	N/A	4 - 6 HRS

[1] As measured through a Ford cup
[2] Recoat period is quoted for 28° - 30°C and 60 - 65% Relative Humidity, these may vary under different conditions
*Use only for 'Plateau Black' finish

HOW TO CHOOSE COLOURS

Browse through Asian Paints Lithos book to choose the right finish and colour combination for you.

ROYALE PLAY LITHOS BOOK

ADDITIONAL INFORMATION

POST PAINTING CARE

Ensure a drying time of at least 2 weeks after painting. For removing stains, sponge clean with a mild soap solution and wipe clean.

TECHNICAL DETAILS

a. Drying time: Dry to recoat after 1st base coat 4 - 6 hours, dry to recoat after 2nd base coat 4 - 6 hours. Surface Dry after topcoat 4- 6 hours

b. Flash point IS101/1987 Part 1, Sec 6: Water-based, non-flammable

PRECAUTIONS

Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.

- Do not apply in higher humid conditions > 80 % RH
- Do not over-thin.
- Tint using Asian Paints machine colourants only.
- Mix well before use.
- Avoid use of wet sponge / water for buffing
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.

SAFETY FEATURES

- Kindly refer to the MSDS for Asian Paints Royale Play Lithos which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour .It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

Version No. VN14/12/21