PRODUCT CODE 5409

Royale Play Teodorico

Asian Paints Teodorico is a lime-based finishing plaster coat, specially formulated for the decoration of prestigious interiors and exteriors, made of hydrated putty, fine marble powder, selected inert and rheological modifiers, which guarantees a perfect workability of the product. With its formulation, Teodorico permits to achieve a uniform and semi-polished finishing coat, similar to marble stone, creating soft and vibrant shades.

PRODUCT FEATURES

AVAILABLE PACKS

Available in 5 kg packages for Teodorico Base, 200 gms packages for Teodorico Gold, Silver and Bronze Mica
Shelf life: The packaged product is guaranteed for 24 months, if stored in the original sealed package and at temperatures between +5°C and +35°C.
Being the product lime-base, there might be an increase of viscosity during stocking

COLOUR

White and Teodorico color card.

PRODUCT TYPE

Base White, Mica Gold, Silver, Bronze

RECOMMENDED USAGE

Teodorico is indicated for the decoration of prestigious interior surfaces. Natural lime plasters represent Teodorico's most suitable substrate, since the product reacts chemically with them, building up a unique "body" able to preserve the lime coating for a longer period of time. In addition Teodorico allows to obtain an extremely elegant decoration of interiors. Following the correct instructions for surface preparation, Teodorico may also be applied on:

- Lime and cement mortars
- Premixed renderings
- Pre-existing lime and gypsum plasters
- Moisture-permeable plasters
- Gypsum plasterboard

FINISH

Visionnaire is available with 3 finishes: Standard, Moon & Travtina.

PERFORMANCE

With its high vapor-permeability, Teodorico is recommended to preserve the permeability rate of the substrate.

IDENTIFICATION

Binder nature: hydrated putty, water-based vinyl versatic copolymers.
Density Teodorico: 1.55 +/- 0.05 g/ml.

HOW TO APPLY

APPLICATION PROCESS

Substrate Preparation
(T=25°C; UR=60°/o) The substrate must be perfectly dry, dust-free, with no humidity and salt stains. On smooth substrates, apply one coat of Pebbltex primer diluted with a brush or with a roller. After at least 4 hours apply one smooth coat of Teodorico, with stainless steel trowel. Remove eventual imperfections or exceeding amounts of product. After at least 12 hours apply a second coat of Teodorico with stainless steel trowel and, before it completely dries out, complete the surface with stainless steel gloss trowel for stuccos. To improve the visual effect, it is recommended to keep the surface wet, compressing it, until obtaining the desired textured.

Decor Process
It is possible to protect and decorate interior surfaces with the application of Royale Play Proctective Clear Coat.

YIELD

PEBBLETEX PRIMER: 5 to 6 m^2/l depending on the kind of substrate and its absorption rate.
TEODORICO: 7 to 8 sq.ft. per coat depending on the kind of substrate and its absorption rate.

TOOLS

APPLICATION: 240 mm Trowel, 3 inch scraper, Yarn Tool, Travertine Trowel.
CLEANING: With water, immediately after their use.

DILUTION

PEBBLETEX PRIMER: Dilute 40-50% with water.
TEODORICO: Ready-to-use.

ADDITIONAL INFORMATION

EFFECTS

Standard Effect
- Prepare the surface with P+P+P (Use texture primer on the top of putty)
- Apply Pebble Tex as a primer (30% dilution with water)on the wall surface.
- Stir the Teodorico material well to mix the strainers & Mica properly.
- Add 2 to 5 % of water if required for easy spreading.
- Apply plain one coat of Pebble Tex using Trowel.
- After 4 to 6 hrs of drying apply one coat of
- Teodorico same as 1st coat using Trowel.
- After 10 to 15 mins buff the surface gently for smoothing.
- Wet the Sponge with water & move on the smoothen surface to open the mica particles which gives metallic look.
- After opening mica particles buff the surface gently using Trowel.

Moon Effect
- Prepare the surface with P+P+P (Use texture primer on the top of putty)
- Apply Pebble Tex as a primer (30% dilution with water)on the wall surface.
- Stir the Teodorico material well to mix the strainers & Mica properly. Apply plain 1st coat of Pebble Tex using Trowel.
- After 4 to 6 hrs of drying apply one coat of Teodorico slightly using more material as compare to 1st coat using Trowel & make the diagonal pattern using Yarn Tool.
- After 10 to 15 mins buff the surface gently for smoothing.

Travtina Effect
- Prepare the surface with P+P+P (Use texture primer on the top of putty)
- Apply Pebble Tex as a primer (30% dilution with water)on the wall surface.
- Stir the Teodorico well to mix the strainers & Mica properly.
- Add 2 to 5 % of water if required for easy spreading. Apply plain 1st coat of Pebble Tex using Trowel.
- After 4 to 6 hrs of drying apply 2nd coat of Teodorico same as 1st coat & create the pattern horizontally using Dubai Trowel.
- After 10 to 15 mins smoothen the pattern using Steel Trowel & buff the surface gently.

ADDITIONAL INFORMATION

WARNING

- Properly mix the product before coloration and application.
- Do not apply on wet surfaces, wait for a maturation period of generally 4 weeks.
- Add Mica to Teodorico before the pigmentation and application of the product, following the instructions described into the technical data sheet Mica.
- The addition of Mica must be gradual and must be done mechanically with mixer for about 2 minutes.

RECOMMENDATIONS

The material must be applied protected from cold and high heat changes during the entire application. Do not apply with air, support and products temperature lower than +10°C or higher than +35°C, nor under direct sun light, nor under superheated surfaces (even if already in shadow). It is advisable to complete each work with materials from the same batch of production.

SAFETY FEATURES

EU Directive 2004/42/CE: Teodorico (decorative paint)
EU limit values for Teodorico (cat ND: 200 g/l (2010)
Teodorico contains maximum 60 g/l of VOC

- Irritating.
- Risk of serious damage to eyes.
- Irritating to the skin.
- Keep out of children.
- Avoid contact with eyes.
- In case of contact with eyes, clean immediately with water and consult a doctor.
- Wear suitable gloves and eyes face protection.
- In case of ingestion of the products, consult immediately a doctor showing him the can or the label of the product Danger labeling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.
- The product must be transported, used and stored according to current standards of hygiene and safety; after the use, do not litter, let the remaining product dry properly and then treat it as special litters.

For further information consult the safety data sheet.
N.B.- The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.