

PRODUCT CODE 5607

Wall 2 Floor Clear

Wall 2 Floor Clear is a water-based polyurethane resin to be used as a protective coat. It is available as Glossy, Satin and Matt.



PRODUCT FEATURES

AVAILABLE PACKS

Each of Glossy, Satin & Matt variant are available in 2 L pack.
The packaged product is guaranteed for 24 months, if stored in the original sealed packages and at the adequate temperatures between +10 and 30°C.

RECOMMENDED USAGE

Wall 2 Floor Clear Finish Protection of vertical and horizontal surfaces of Wall 2 Floor system.

IDENTIFICATION

Density of the mixture: 1.04 gr/ml +/- 3%

COLOUR

Transparent. Cannot be tinted.

HOW TO APPLY

PREPARATION & APPLICATION

Blend Clear Finish A in order to avoid sediments. Add slowly Clear Finish B into Clear Finish A while mixing manually for 45-60 seconds approximately. You can also mix with a slow speed drill for 1 minute approximately. The mixture must not contain lumps, portions of the two components unmixed, impurities. Apply 1st coat using sponge roller. Allow it to dry for 3-4 hours. Clean the surface and apply 2nd coat using sponge roller. Allow it to dry for 3-4 hours.

TOOLS CLEANING

With Water

YIELD

Forced coverage of 5-6 m²/L in two coats.

DILUTION

When the mixture is complete (1.5 L of component A + 0.5 L of component B), proceed with the dilution with 10% of water.
Pot life: 60 minutes.

ADDITIONAL INFORMATION

SAFETY FEATURES

- > EU directive 2004/42/CE: Clear Finish Bi-Component (bi-component paints with high performances) EU limit value for Clear Finish Bi-Component (cat A/j): 140 g/l (2010) Clear Finish Bi-Component contains maximum 140 g/l of V.O.C. It contains isocyanate: see the manufacturer's technical data sheet. Harmful if inhaled / Irritating to respiratory system / may cause sensitization by skin contact / Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety; let the residues dry out completely and treat them as special waste. For more information see the safety data sheet.
- > The information herein is provided to the best of technical and scientific knowledge and based on experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets.

RECOMMENDATIONS

During the preparation of the substrate and application of the products, it is recommended the correct use of tools and individual protective devices (dpi). Keep the product protected from intense heat or from temperature lower than +5°C. If stored to as temperature close to +5°C, it is suggested to keep the product in an area with a temperature not lower than 10°C. Do not heat the products using a direct source of heat, flame, hot body or similar.

Low temperatures increase the viscosity in the bucket making it difficult to use and extend or inhibit the drying and hardening process of the various products. If possible, use the same batch of production. If different batches of production are used, it is recommended to mix them in order to avoid slight different shades.