

|                                                                                   |                                                                                                       |                                       |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------|
|  | Company Name:<br><b>ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር</b><br><b>KADISCO CHEMICAL INDUSTRY PVT LTD CO</b> | Document No.:<br><b>PS/KCI/WO/004</b> |
| Revision: 0                                                                       | Document Title<br><b>Product Specification</b>                                                        | Page 1 of 1                           |

## **KADISCO 2K POLYURETHANE SANDING SEALER.**

### **DESCRIPTION.**

Kadisco 2K Polyester Sanding Sealer for wood applications.

### **USES.**

For priming wood in preparation for top coat application. It gives extra strength and durability for all wood and allows the top coat to form a strong layer on the surface. It is especially useful when used for such areas as doors, parquets and other household furnishings.

### **PROPERTIES.**

|                       |                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>Finish</b>         | Matt                                                                                                                     |
| <b>Solvent</b>        | Acrylic Thinner                                                                                                          |
| <b>Hardener</b>       | 10% of Kadisco Polyester Hardener (1 half litre can for 1 gallon of paint)                                               |
| <b>Thinning</b>       | For brush application: max 10% with Acrylic thinner. Check viscosity during use.<br>For spray application: 10-15%        |
| <b>Drying Time</b>    | Touch dry between 15-30 minutes depending on temperature, humidity and type of wood used. Sand after 24 hours of drying. |
| <b>Spreading Rate</b> | 5-6m <sup>2</sup> /kg                                                                                                    |
| <b>Colour range</b>   | Colourless or white                                                                                                      |
| <b>Package</b>        | Available in 1ltr.and 4ltr cans                                                                                          |
| <b>Coating</b>        | One or Two Coats is sufficient                                                                                           |
| <b>Storage</b>        | Do not keep it at a temperature below 5 <sup>0</sup> C.                                                                  |

### **INSTRUCTIONS FOR USE.**

#### **a) Surface preparation:**

- Surfaces should be clean, dry and free from all defective or poorly adhering material such as dust or oily materials. All surfaces should be thoroughly rubbed down using a suitable sanding paper and then dusted off.

#### **b) Application:**

- Application is done by brush or spray.
- Mix the sealer with 10% of polyester hardener before painting. This is equivalent to 1 half litre can of hardener for 1 gallon of paint.
- Thin the mixture using Kadisco Acrylic thinner according to above instruction.
- One or two coats should be sufficient.
- Clean all tools and equipment immediately after use with Thinner.

Precondition: Use mask and gloves when applying the product.

|                                                                                   |                                                                                                       |                                       |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------|
|  | Company Name:<br><b>ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር</b><br><b>KADISCO CHEMICAL INDUSTRY PVT LTD CO</b> | Document No.:<br><b>PS/KCI/WO/004</b> |
| <b>Revision: 0</b>                                                                | Document Title<br><b>Product Specification</b>                                                        | <b>Page 2 of 1</b>                    |

|                                                                                   |                                                                                                       |                                       |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------|
|  | Company Name:<br><b>ካዲስኮ ኬሚካል ኢንዱስትሪ ታ.የተ.የግ. ማኅበር</b><br><b>KADISCO CHEMICAL INDUSTRY PVT LTD CO</b> | Document No.:<br><b>PS/KCI/WO/004</b> |
| <b>Revision: 0</b>                                                                | Document Title<br><b>Product Specification</b>                                                        | <b>Page 3 of 1</b>                    |