

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/005
Revision: 0	Document Title Product Specification	Page 1 of 2

KADISCO ALKYD VARNISH.

DESCRIPTION.

Kadisco Alkyd Varnish is an alkyd based varnish.

USES.

It is used for the decoration and protection of exterior and interior wood work surfaces where a hard, durable and clear coating is required. The transparent finish enhances the natural beauty of wood whilst providing a lasting protection.

PROPERTIES.

Finish	Gloss and Matt
Solvent	White Spirit
Durability	When correctly applied a life expectancy 5–7 years can be expected.
Toxicity	Non Toxic.
Drying Time	Single coat at standard thickness touch dry, 4-6 hours. Recoat after 12 hours.
Spreading Rate	A guide to the practical coverage which can be achieved under normal conditions is 8-10m ² /ltr
Colour range	See KADISCO Synthetic Paint Colour Card.
Package	Available in 1ltr.and 4ltr cans as well as 100ltr
Coating	Two coats of Kadisco alkyd varnish, especially for exterior finish.
Limitations	Do not over thin. When applying to new wood surfaces, apply the proper wood primer before coating with Kadisco Alkyd Varnish. Do not apply if risk of rain or when air/surface temperature is below 5 ⁰ C. During application or drying periods, protect from frost, rain and direct sunlight.
Storage	Do not keep it at a temperature below 5 ⁰ C.

INSTRUCTIONS FOR USE.

a) Surface preparation:

- Surfaces should be clean, dry and free from all defective or poorly adhering material such as dirt, rust and oily materials etc. All surfaces should be thoroughly rubbed down using a suitable sanding paper and then dusted off.

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/005
Revision: 0	Document Title Product Specification	Page 2 of 2

- When applying to previously stained or varnished surfaces, rub down thoroughly along the wood to provide a good surface for subsequent coats.
- When sealing new or bare surfaces use thinned gloss varnish.

b) Application:

- Application is done by brush and roller.
- Thinning: For sealing new or bare surfaces add up to 2 part of turpentine (white spirit) or “Aquaragia” to 10 parts of varnish. For normal use do not thin more than 25%.
- Clean all tool and equipment immediately after use with turpentine (white spirit).

ADVANTAGES.

- **Good colour retention.**
- **High Gloss.**

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ታ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/005
Revision: 0	Document Title Product Specification	Page 3 of 2