

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/009
Revision: 0	Document Title Product Specification	Page 1 of 2

6.0 KADISCO COLOURED WOOD STAIN.

DESCRIPTION.

Kadisco Coloured Wood Stain for colouring different types of wood to the users requirements.

USES.

Wood Stains are used for wood protection and for colouring. It can also be used for additional protection on transparent application due to its high penetration.

PROPERTIES.

Finish	Gloss and Matt
Solvent	NC Thinner
Specific Gravity	0.85g/cc
Solid content by weight	47% (normal)
Durability	When correctly applied a life expectancy 7–10 years can be expected. External application 4-5 years.
Thinning	Not Necessary. But to get lighter colours then standard add white spirit to the requirement of the users colour.
Toxicity	Non Toxic.
Drying Time	Touch dry up to 30 minutes depending on temperature, humidity and type of wood used. Completely dry after 24 hrs, apply each coat after 24hrs.
Viscosity	Low
Spreading Rate	Depending on absorption of the wood 10-14m ² /kg
Colour range	See wood samples
Package	Available in 1ltr.and 4ltr cans
Coating	One coat of colour and two coats of transparent
Limitations	Do not over thin. Prepare surface as required. Do not apply if risk of rain or when air/surface temperature is below 5 ⁰ C. During application or drying periods, protect from frost, rain and direct sunlight
Storage	Do not keep it at a temperature below 5 ⁰ C.

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/009
Revision: 0	Document Title Product Specification	Page 2 of 2

INSTRUCTIONS FOR USE.

a) Surface preparation:

- Surfaces should be clean, dry and free from all defective or poorly adhering material such as dirt, rust and oily materials etc. All surfaces should be thoroughly rubbed down using a suitable sanding paper and then dusted off.

b) Application:

- Application is done by brush or Sponge.
- For internal as a top coat use any type of varnish, lacquer etc.
- Apply the Top Coats after 24 hours for best results.

ADVANTAGES.

- Use of stain for colouring wood allows for deeper penetration, thus longer lasting colour retention
- Gives protection for the wood, especially for external applications of wood
- Fast drying
- Can use Varnishes and lacquers as final coat to get the desired finish
- Excellent properties for external use without using varnish. Use the clear as top coat