

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/AD/006
Revision: 0	Document Title: Product Specification	Page No.: Page 1 of 1

KADISCO HALOGINATING PRIMER

DESCRIPTION.

KADISCO HALOGINATINGPRIMER is a mixture of halogenating chemicals and solvents.

USES.

KADISCO HALOGINATING PRIMER is suitable for washing SBR and TR soles before bonding with polyurethane adhesives such as KADIFIX II.

PROPERTIES.

Base	Clear
Storage	Up to One week at 21 ⁰ C

INSTRUCTIONS FOR USE.

a) Surface preparation:

- Surfaces should be clean, dry and free from all defective or poorly adhering material such as dirt, rust and oily materials etc.

b) Application:

- KADISCO HALOGINATING PRIMER is applied with a brush.
- Spread evenly a thin layer of primer on the surfaces to be joined.
- Wait for at least 20 minutes before spreading the polyurethane adhesive.
- Soles can be used for up to 1 week after priming.

LIMITATIONS.

- Halogenated primer must be used immediately after preparation.
- Ensure it is not exposed to light and humidity.
- Ensure it does not come in contact with metal.

PACKAGING.

KADISCO HALOGINATING PRIMER is available in customers own container.
 Keep away from fires, sparks etc.

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ጋ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/AD/006
Revision: 0	Document Title: Product Specification	Page No.: Page 2 of 1