

Kadisco Wall Plaster

Product Description

An acrylic co-polymer based filler containing alkali resisting pigments, for the filling of surface irregularities and indentations, hairline surface cracks etc. It helps to produce a smooth and level surface prior to painting.

Recommended Areas of Application

Area of Use: Interior

Substrate: Concrete, Plaster, Masonry, Gypsum.

Technical Data

Sheen Variants: Matt

Colours: White

Volume Solids: 52% $\pm$ 2%

Theoretical Covering Capacity

Solely dependent on the surface profile and the extent of filling required. However, as a guidance only 2-3 m²/Kg may be considered for a reasonably smooth plastered surface.

Practical Covering Capacity

For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	25°C	3 hours	6 hours	Indefinite
	35°C	2 hours	4 hours	Indefinite
	45°C	1 hours	2 hours	Indefinite

Application Data

Method of application: Putty knife or Trowel

Thinner: Sweet water

Thinning ratio (by vol.): N.A.

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Kadisco Wall Plaster

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

TYPICAL PAINT SYSTEM
1 coat Kadisco Wall Primer
2 coats Kadisco Wall Plaster
2 coats Interior Emulsions
For alternate system suggestion please contact Sales Representative

Storage, Safety Information and Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life of up to 12 months from the date of manufacture.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.