

Kadisco Wall Putty

Product Description

Kadisco Wall Putty and crack filler is a single pack, ready to use flexible filler material composed of high quality durable acrylic emulsion polymer, selected graded fillers and additives. It is designed for filling joints, cracks etc. unlike conventional fillers, it has excellent bonding and elastic properties. Can be used for filling cracks up to 6 mm.

Recommended Areas of Application

Area of Use: Interior and Exterior

Substrate: Concrete, plaster, masonry, gypsum, brick work or block work.

Technical Data

Sheen Variants: Matt

Consistency: Non sagging paste

Colour: White

Full curing time: 7 days

Volume Solids: 75% $\pm$ 2%

Theoretical Covering Capacity		
Recommended Dry Film Thickness per coat		Theoretical Spread rate
Typical	1-2 mm	1.5 – 2.0 m ² /kg.

Practical Covering Capacity
For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	25°C	3 hours	12 hours	Indefinite
	35°C	2 hours	10 hours	Indefinite
	45°C	1 hours	8 hours	Indefinite

Application Data

Method of application: Putty knife or Trowel

Thinner: Sweet water

Thinning ratio (by vol.): N.A.

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Kadisco Wall Putty

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 95% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.
- Kadisco Wall Putty is used for filling surface irregularities, indentations and undulations to produce a smooth and level surface prior to painting
- Kadisco Wall Putty can also be used for renovation and refurbishment of existing buildings.
- Kadisco Wall Putty is adherent to most surfaces – old and new.
- Because of its excellent hiding power, it can cover any blemishes or imperfections on the existing surface.

TYPICAL PAINT SYSTEM
1 coat Kadisco Wall Primer
2 coats Kadisco Wall Putty
2 coats Exterior Emulsions
For alternate system suggestion please contact Sales Representative

Storage, Safety Information and Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life of up to 12 months from the date of manufacture.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.