

	Company Name: ካዲስኮ ኬሚካል ኢንዱስትሪ ኃ.የተ.የግ. ማኅበር KADISCO CHEMICAL INDUSTRY PVT LTD CO	Document No.: PS/KCI/WO/007
Revision: 0	Document Title Product Specification	Page 1 of 1

KADIVIL 318

KADIVIL 318 is a plasticized water dispersion of polyvinyl acetate with high solids and high viscosity.

1	Supply specifications	U.M.	Values
	Solid content	%	>50
	Ph		4.5±0.5
	Viscosity *	mPa.s	43000±10000
2	Typical values		
	Density at 20°C	Kg/dm ³	1.1
	Minimum film forming temperature	°C	0
	Prevailing particle size	µm	0.6÷2
	Residual monomer	%	0.1 max
	Emulsifying system	Polyvinyl alcohol	
	Mechanical stability	-	Excellent

*RVT 20 rpm, spindle 7, 23°C

Applications

Book binding, paper, leather and textile adhesives. Building adhesives and plasters.

Specific properties

KADIVIL 318 is particularly suitable to prepare adhesives to use on automatic machines for the production of boxes and cases.

Packaging

KADIVIL 318 is available in 4lit., 20lit and 100lit.

KADIVIL 318 is stable for 6months, when stored between +5 and +40°C.