

Technical Data Sheet - Architectural Coatings

PVA Primer

Product Description

A water based primer, based on PVA co-polymer formulated to penetrate into and seal the surface. It provides a sound base for subsequent interior emulsion coatings from the Kadisco Asian Paints range.

Recommended Areas of Application

Area of Use : Interior
Substrate : Concrete, Plaster, Brickwork, Block work, Wood

Technical Data

Sheen Variants : Matt
Colours : White
Volume Solids : 32% $\pm$ 2%

Theoretical Covering Capacity	Recommended Dry Film Thickness per Coat		Theoretical Spread Rate
	Minimum	20 microns	16.0 m ² /Ltr
	Typical	27.5 microns	11.6 m ² /Ltr
	Maximum	35 microns	9.1 m ² /Ltr

Practical Covering Capacity : For estimation of practical covering capacity, following factors to be considered: surface profile, uneven application, application losses, losses in container and equipment, etc.

Drying time	Substrate Temperature	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	25°C	3 hours	6 hours	Indefinite
	35°C	2 hours	5 hours	Indefinite
	45°C	1 hour	4 hours	Indefinite

Application Data

Method of application : Roller or brush
Thinner : Sweet water
Thinning ratio (by vol.) : Use 5% to 10% sweet water for ease of application

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.
- If surface is previously painted, ensure that all peeling or flaking paint is removed completely.
- Thoroughly dust down the entire surface.

Note: Fungal growth should be treated with Fungicidal Solution. After drying, one coat of Anti Fungal primer and Penetrating Sealer can be applied if required.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.
- **Brush or Roller** : Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

TYPICAL PAINT SYSTEM

Interior –

1 coat x PVA Primer

2 coats x Wall Plaster 96 (For Royale Silk - 1 coat of PVA Primer to be applied after Wall Plaster 96)

2 coats x Royale Luxury Matt/Silk Emulsion

* For alternate system suggestion please contact Kadisco Asian Paints Sales Representative

Storage, Safety Information And Precautions

Safety Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 months from the date of manufacture.

First-Aid

- **Eyes** : In the event of accidental splashes, flush eyes with water immediately and obtain medical advice.
- **Skin** : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- **Inhalation** : Move patient to fresh air, loosen collar and keep patient rested.
- **Ingestion** : Do not induce vomiting. Obtain immediate medical attention.
- **Dispose** in landfill only.

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.

This Technical Data Sheet supersedes those previously issued with immediate effect