

Technical Data Sheet - Architectural Coatings

Royale Luxury Silk Emulsion

Product Description

A luxury product formulated using Acrylic co-polymer and containing titanium dioxide and other high grade light fast alkali resisting pigments. Royale Luxury Silk Emulsion has outstanding scrub resistance and washability, resistance to fungus and algae, easy cleaning properties, dirt resistance, colour retention properties and an appealing smooth finish with a silky sheen. It is easy to apply and being water thinnable, environment friendly, and is thus an ideal decorative finish particularly for the interior.

Recommended Areas Of Application

- **Area of Use** : Interior
- **Substrate** : Concrete, plaster, masonry, gypsum, timber

Technical Data

Sheen Variants	:	Silky Sheen
Volume Solids	:	32% ± 2%
Colours	:	As per shade card and available in various shades through Colour tinting system.

Theoretical Capacity	Covering	Recommended Dry Film Thickness per coat		Theoretical Spread rate
		Minimum	30 Microns	10.3 m ² / Ltr.
		Typical	37.5 Microns	8.2 m ² / Ltr.
		Maximum	45 Microns	6.8 m ² / Ltr.

Practical Capacity	Covering	:	For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment, etc.
---------------------------	-----------------	---	---

Drying time	Substrate temp.	Touch dry	Overcoating interval	
			Minimum	Maximum
	25°C	6 Hours	12 Hours	Indefinite
	35°C	3 Hours	8 Hours	
	45°C	1.5 Hours	4 Hours	

Application Data

Method of application	: Brush, Roller or Spray application.
Thinner	: Sweet water
Thinning ratio (by vol.)	: Use 5% maximum for ease of application depending on the method of application.

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Fungicidal Solution. After drying, one coat of Anti Fungal primer and Penetrating Sealer can be applied if required.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Brush or Roller: Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

Conventional Spray: Use normal spray equipment

Airless Spray: May also be used if required.

Typical Paint System

- 1 coat x Alkali Resistant Primer / PVA Primer
- 2 coat x Wall Plaster 96
- 1 coat x Alkali Resistant Primer / PVA Primer
- 2 coats x Royale Luxury Matt Emulsion

For alternate system suggestion please contact Kadisco Asian Paints Sales Representative

Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Shelf life up to 24 months from the date of manufacture.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.

Version 1, Aug'2025