

## Material Safety Data Sheet

**ROAD MARKING PAINT****1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY**

Product Name : Road Marking Paint  
Product Type : Acrylic Chlorinated Rubber type  
Supplier : Berger Paints Emirates Limited  
P O Box 27524, Dubai, UAE.  
Telephone Number : 00-9714-391000  
Emergency Telephone Number : 00-9714-391078

**2. COMPOSITION/INFORMATION ON INGREDIENTS :**

	<u>Weight%</u>	<u>CAS Number</u>	<u>LEL Vol%</u>	<u>ACGIH TLV-TWA</u>
• Acrylic Resin	> 12	-	-	-
• Chlorinated rubber	< 10	-	-	-
• Titanium Dioxide	> 15	13463-67-7	NA	10 mg/m <sup>3</sup>
• Xylene	> 10	1330-20-7	1.2	100 ppm
• Calcium Carbonate	> 35	1317-65-3	-	10 mg/m <sup>3</sup>
• N-Butyl Acetate	> 7	123-86-4	-	150 ppm

**3. HAZARDS IDENTIFICATION :**

- Hazards identification of the preparation :  
R-10 : Flammable  
R-20/21/22 : Harmful by halation, in contact with skin and if swallowed.  
R-38 : Irritating to skin.

Global presence of the Group

**Berger:** Bahrain, Barbados, Jamaica, Oman, Singapore, Trinidad & Tobago, UAE. **Taubmans:** Fiji, Samoa **Scib Paints:** Egypt**Asian Paints:** Bangladesh, India, Indonesia, Nepal, Sri Lanka **Apco Coatings:** Fiji, Solomon Islands, Tonga, Vanuatu **Kadisco:** Ethiopia

4. **FIRST AID MEASURES :**

General	: Remove contaminated clothing.
First Aid - Inhalation	: Remove to fresh air. If rapid recovery does not occur, obtain medical attention.
First Aid - Skin	: Remove contaminated clothing immediately. Wash skin thoroughly with soap and water.
First Aid - Eye	: Irrigate copiously with clean, fresh water for atleast 10 minutes, holding the eye lids apart and seek medical advice.
First Aid - Ingestion	: Do not induce vomiting. Obtain immediate medical attention.

5. **FIRE FIGHTING MEASURES :**

Specific hazards	: Fire will produce dense, black smoke. Inhalation of decomposition products may cause serious health hazards..
Extinguishing media	: Water spray-mist, foam, dry chemical powder, carbon dioxide, sand.
Unsuitable extinguishing media	: Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES :**

Personal precautions	: Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames, Remove ignition sources, Avoid sparks.
Personal protection	: Wear PVC gloves, safety boots. Wear full face-piece respiratory with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.
Environmental pre cautions	: Prevent contamination of soil and water.
Processing for Cleaning/ Collecting	: Contain and collect spillage with non-combustible absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according to local regulation.

7. **HANDLING AND STORAGE :**

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mists. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharges.

Handling temperature	: Ambient
Storage	: Keep container tightly closed and in a well ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas.
Storage temperature	: Ambient.

**Global presence of the Group**

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION :**

- Engineering Control Measures : Use only in well ventilated areas.  
Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Hand protection : PVC gloves. Barrier creams may help to protect the exposed areas of the skin.  
Eye protection : Use safety eyewear designed to protect against splash of products.

9. **PHYSICAL AND CHEMICAL PROPERTIES :**

- Physical state : Liquid  
Odour : Like organic solvents  
Safety related information : Value  
Flash Point : 23 - 29°C (Abel closed cup)  
Ignition temperature : > 350°C  
Initial Boiling Point : 137°C (Based on Xylene)  
Vapour Density (Vs. Air) : Heavier  
Evaporation Rate : Slower  
(Vs n-Bu Acetate)  
Density at 25°C : 1.4 - 1.6 gm/cc  
Solubility in water : Negligible.

10. **STABILITY/REACTIVITY :**

- Stability : Stable under normal conditions.  
Conditions to avoid : Heat, flames, and sparks, Caustic soda induce a vigorous polymerization at a temperature around 200°C.  
Materials to avoid : Strong Oxidizing agents. Caustic Soda.  
Hazardous decomposition products : Unknown.

11. **TOXICOLOGICAL INFORMATION :**

- Basis for assessment : This product was not tested but the information given is based on the known toxicological data of the Constituents.  
Acute toxicity - oral : LD 50 expected to be > 2000 mg/kg based on Xylene  
Acute toxicity - dermal : LD 50 expected to be > 2000 mg/kg based on Xylene  
Eye irritation : The liquid splashed in the eyes may cause irritation.  
Skin irritation : Irritant.

12. **ECOLOGICAL INFORMATION** : Avoid contamination of earth, rivers, lakes or sewers.

- Water contamination class : 2 (self classification).

**Global presence of the Group**

**Berger:** Bahrain, Barbados, Jamaica, Oman, Singapore, Trinidad & Tobago, UAE. **Taubmans:** Fiji, Samoa **Scib Paints:** Egypt

**Asian Paints:** Bangladesh, India, Indonesia, Nepal, Sri Lanka **Apco Coatings:** Fiji, Solomon Islands, Tonga, Vanuatu **Kadisco:** Ethiopia

13. **DISPOSAL CONSIDERATIONS** :

The generation of waste should be avoided or minimized wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way.

14. **TRANSPORT INFORMATION** :

UN Number : 1263  
IMCO Class : 3.3  
Page Number : 3149  
Marine Pollutant : Yes  
Proper shipping name : Paint.

15. **REGULATORY INFORMATION** :

- EC Classification : Flammable. Harmful.  
Contains : Xylene
- EC Risk phrases  
R-10 : Flammable.  
R-20/21/22 : Harmful by inhalation, in contact with skin and if swallowed  
R-38 : Irritating to skin.
- EC Safety Phrases  
S-24 : Avoid contact with skin  
S-25 : Avoid contact with eyes.  
S-36/37 : Wear suitable protective clothing and gloves  
S-51 : Use only in well ventilated areas.

16. **DISCLAIMER** :

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.

Version: 1 Oct-2017

**Global presence of the Group**

**Berger:** Bahrain, Barbados, Jamaica, Oman, Singapore, Trinidad & Tobago, UAE. **Taubmans:** Fiji, Samoa **Scib Paints:** Egypt

**Asian Paints:** Bangladesh, India, Indonesia, Nepal, Sri Lanka **Apco Coatings:** Fiji, Solomon Islands, Tonga, Vanuatu **Kadisco:** Ethiopia