

Technical Data Architecture Coatings

Mumtaz Double Concentration Interior Emulsion

Product Description

Mumtaz Double concentration Interior Emulsion is an innovative, new generation product to get maximum coverage and finish. It is designed to be thinned in 1:1 ratio, yet gives excellent coverage in two coats for most of the interior surface. High technology used in this product, makes it easy to apply and gives best in class washability and smoothness. Mumtaz has been developed to suit the requirement of Oman consumers and painting practices followed in terms of application and economy.

Recommended Areas of Application

Area of Use : Interior
Substrate : Concrete, plaster, fibrous cement sheeting, stucco/rough, concrete blocks, brick work, timber and weatherboards.

Technical Data

Shade / Colour Range : White and mumtaz colour card
Composition : High quality Co-polymeric Emulsion, High reflective index/ high coloristic value pigments, micronized extenders and hi-tech additives.
%Volume Solids : 41 ± 2 % (for most of the shades)
Pack Size : 25 Kg & 6 Kg for white
22 Kg and 5.5 Kg for shades
Theoretical Coverage : 10.25 Sqm. / Ltr. @ 40µ DFT
Practical coverage : Practical Coverage may depend on surface profile, method of application weather conditions.

	Surface dry	Touch dry	Recoatibility	Hard dry
Drying time 30°C:	15 minutes	30 minutes	4 hours	16 - 18 hours

Application Data

Method of application : Brush, Roller
Thinner : Municipal / Potable Water
Thinning ratio (by vol.) : 100% or as required

Surface Preparation

Remove dust, dirt, grease, loos and flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface if mould or fungus is present on the concrete wall, then treat with antimicrobial solution.

Applications Details

- Apply one coat of Decora Primer Sealer.
- After drying, sand lightly, apply BERGER Decora Stucco Putty. After drying, sand it with emery paper 320 and topcoat with Mumtaz Double Concentration Emulsion.
- For hiding dark shades of contrast colors, 3 coats may be required
- This product is not suitable for Exteriors or for area continuously exposed to direct sunlight Before applying the paint, make sure that the area is completely dried and free from fungi, water leakage or seepage.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action Apply uniformly by convenient method of application, after thinning the paint to obtain the desired level of consistency 2nd coat to be applied only after 4-6 hrs of the 1st coat.

RECOMMENDED PAINT SYSTEM

One coat x Decora Primer Sealer / Decora PVA Primer

Two coats x Decora Super Stucco Putty

Two coats x Mumtaz Double Concentration Emulsion

* For detailed system recommendation based on specific requirements please contact Asian Paints representative.

Storage, Safety Information And Precautions

Flammability and Transport Information: Non flammable

Safety information and precautions:

- Do not apply at temperature below 10°C
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eye, wear suitable Personal Protective Equipments such as overalls goggles, dust masks and gloves
- Dispose in landfills only

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect



**For enquiries, feedback and complaints,
please call Toll-Free number 80001790
or write to us at
weassure.oman@asianpaints.com**