

Technical Data Architecture Coatings

Royale Play Italian Stucco

Product Description

Royale Play Italian Stucco is a top of the range water-based Venetian finish which creates attractive boundless marble like effects on various surfaces. This product is a carefully engineered one to get the best of the skill of an applicator and imagination of an artist.

Designed Use

- Luxury range interior finish
- To create a natural marble look respecting ancient tradition
- Unlimited marble effects
- Hygienic and anti-fungal
- Glossy or satin finishes are possible
- Decorative effects to redefine surroundings
- User and eco friendly
- Dirt resistant and non-toxic

Technical Data

Finish	: Smooth, Satin and Glossy
Colours	: As per colour card of custom-made colour
Solids (% by volume)	: 54 ± 2
Thinner/Cleaner	: Water
Spread Rate	: Solely dependent on the surface profile and the extent of finish required. However, as a guideline only 3.5 m ² may be considered for reasonably smooth plastered surface.
Drying Time	: Thorough drying for 6 hours after application of final coat under ambient temperature of 35°C.

Surface Preparation

Ensure the surface is clean, dry and free from all loose or flaking particles. Apply the recommended primer for the substrate, followed by your choice of Royale Luxury Matt Base Coat prior to application of Royale Play Italian Stucco.

System Recommendation: Royale Play Italian Stucco can be applied under normal conditions to add value to the conventional systems.

- a) On fresh plaster**
- : 1 coat of Value PVA Primer Sealer, 2 coats of Stucco, 1 coat of Royale Matt Base Coat and finally apply Royale Play Italian Stucco.

- b) On previously painted surface** : Royale Luxury Matt Base Coat followed by Royale Play Italian Stucco.
- c) On wooden surfaces** : 1 coat of Synthetic Wood Primer, 1 coat of Synthetic Undercoat, Royale Luxury Matt Base Coat and finally 1 coat of Royale Play Italian Stucco.

For a smooth and polished finish, top the stucco finish with a coat of polish.

Application Details

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point. This material is ready to use. Dilution with water is not recommended.

- Apply first coat of stucco and wait for 1-2 hours.
- After the second coat, smooth the surface using the other colour and wait for 1-2 hours.
- Apply the third coat if needed, sleeking the product with a metal spatula for a polished effect.

Storage, Safety Information And Precautions

Storage and Handling:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 month is from the date of manufacture.

First-Aid

- Eyes : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation : Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion : Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

NB: The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect