

# Technical Data Architectural Coating

## SUPREME ACRYLIC EMULSION (ABF)

### Product Description

A high quality Acrylic co-polymer latex pigmented with titanium dioxide and other light fast and alkali resisting pigments. It has good flow and leveling and colour retention properties. Possesses good washability and is an ideal smooth and matt coating for internal area. In addition this paint provides excellent anti bacterial and fungal protection due to presence of superior antimicrobial agents present

### Recommended Areas of Application

**Area of use** : Interior  
**Substrate** : Concrete, plaster, masonry, brickwork, block work, gypsum, timber

### Technical Data

**Sheen Variants** : Matt, Smooth  
**Colours** : As per shade card  
**Volume Solids** : 34% ± 2%

Recommended Dry Film Thickness per coat		Theoretical Spread rate
Minimum	40 microns	8.50 m <sup>2</sup> /Ltr
Maximum	60 microns	5.66 m <sup>2</sup> /Ltr
Typical	50 microns	6.80 m <sup>2</sup> /Ltr

**Practical Covering Capacity** For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

	Substrate temp.	Touch dry	Overcoating Interval	
			Minimum	Maximum
Drying time	25°C	3 hours	24 hours	Indefinite
	35°C	2 Hours	18 hours	
	45°C	1 Hours	12 hours	

## Application Data

**Method of application** : Brush, Roller or Spray application  
**Thinner** : Sweet water  
**Thinning ratio (by vol.)** : Use 10% to 15% for ease of application depending on the method of application

## Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

## Applications Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action

**Brush or Roller:** Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

**Conventional Spray:** Use normal spray equipment

## Typical Paint System

1 coat x Bergercoat Primer Sealer

2 coats x Bergercoat Stucco

2 coats x Select Acrylic Emulsion ABF

For alternate system suggestion please contact Berger Paints Sales Representative

## Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Shelf life up to 12 months from the date of manufacture.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.

## First Aid

- **Eyes** : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- **Skin** : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- **Inhalation** : Move patient to fresh air, loosen collar and keep patient rested.
- **Ingestion** : Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

## Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.